

American Electric Power 1 Riverside Plaza Columbus, 0H 43215-2373 AERoom

November 21, 2013

Ms. Becky L. France Water Permit Writer Virginia Department of Environmental Quality 3019 Peters Creek Road Roanoke, Virginia 24019

Re: Appalachian Power Company

Reusens Hydroelectric Plant VPDES Permit Renewal Application

VPDES Permit No. VA0087114



Dear Ms. France:

Please find enclosed, one (1) original copy of a completed VPDES permit renewal application for the above referenced facility and permit. Contained within the application packages are the following:

- EPA General Form 1
- EPA Form 2C for Outfalls 001, 002, 003, 004, 005 and 006
- Figure 1 USGS Site Location Map
- Figure 2 VPDES Water Balance Diagram
- Appendix A Notes
- Appendix B Outfall Descriptions
- Appendix C Approved 8-Hour Composite Sampling during Previous Renewal (2008)
- Appendix D Summary of Discharge Monitoring Reports
- VPDES Permit Application Addendum

As discussed in the enclosed application and previously communicated to DEQ, Reusens Hydroelectric Plant is currently inoperable and has not been operated since March 2011. At the time of this submittal, it is unknown when the Plant will resume operation. If you have any questions or need additional information, please contact Lindsey Forhan of my staff at (614) 716-2275 or at Igforhan@aep.com.

Sincerely,

Alan R. Wood, P.E.

Director, Water & Ecological Resource Services

Enclosure

APPALACHIAN POWER COMPANY

Reusens Hydroelectric Plant Amherst County, Virginia

VPDES Permit Renewal Application

Virginia Department of Environmental Quality VPDES Permit No. VA0087114



Prepared by:

American Electric Power Service Corporation
Environmental Services
1 Riverside Plaza
Columbus, Ohio 43215

Prepared for:

Appalachian Power Company Reusens Hydroelectric Plant 4200 Hydro Street Lynchburg, Virginia 24503



November 2013

TABLE OF CONTENTS

- Public Notice Billing Information Form
- EPA General Form 1
- EPA Form 2C for Outfalls 001, 002, 003, 004, 005 and 006
- Figure 1 USGS Site Location Map
- Figure 2 VPDES Water Balance Diagram
- Appendix A Notes
- Appendix B Outfall Descriptions
- Appendix C Approved 8-Hour Composite Sampling during Previous Renewal (2008)
- Appendix D Summary of Discharge Monitoring Reports
- VPDES Permit Application Addendum

PUBLIC NOTICE BILLING INFORMATION FORM

I hereby authorize the Department of Environmental Quality to have the cost of publishing a public notice billed to the Agent/Department shown below. The public notice will be published once a week for two consecutive weeks in accordance with 9 VAC 25-31-290.C.2:

Newspaper Name:		
Agent/Department to be	billed:	Alan R. Wood, P.E.
Owner:		c/o Appalachian Power Company
Applicant's Address:	•	1 Riverside Plaza
		Columbus, OH 43215
		· · · · · · · · · · · · · · · · · · ·
Agent's Telephone No:		(614) 716-1233
Authorizing Agent:	Signale	The Hand
	Alan F Printed	R. Wood, P.E. Name
	Direct Title	or, Water & Ecological Resource Services
Facility Name:	APCo	- Reusens Hydroelectric Plant
Permit No.	<u>VA00</u>	87114
Please return to:	Depart 3019 Pe Roanok	L. France ment of Environmental Quality eters Creek Road te, VA 24019

Please print or type in the unshaded areas only (fill-in areas are spaced for elite type, i.e., 12 char	racters/inch).		For Approved. OMB N			es 5-31-92
FORM	U.S. ENVI		PROTECTION AGENCY	I. EPA I.D. NU		T/A C
1 SEPA	Cons	olidated Pe	ermits Program	F. VAD9882		D
GENERAL (Re	ad the "Ge	neral Instru	ctions" before starting.)		L INSTRUCTI	
		- 22 2 2 2 2 2		If a preprinted la	abel has bee	en provided,
I. EPA I.D. NUMBER	VAI	D9882042	210.	l information care	itully: if an	v of it is
III. FACILITY NAME	eusens l	Hydroeled	tric Plant	incorrect, cross correct data in the below. Also, if an	ne appropriat y of the prepr	e fill-in area inted data is
C	o Americ	can Electi	ic Power	absent (the area	information	of the label that should
V. FACILITY MAILING LIST 1 Riversi	de Plaza	Columb	us, Ohio 43215	appear), please print area(s) below.	If the label	is complete
	ر الله الله			and correct, you I, III, V, and VI(e: completed regard	xcept VI-B wi dless). Compl	nich must be ete all items
VI, FACILITY LOCATION 4200 Hyd	ro Street	Lynchbu	irg, Virginia 24503	if no label has be instructions for of and for the legal this data is collec	letailed item authorization	descriptions
II. POLLUTANT CHARACTERISTICS						
INSTRUCTIONS: Complete A through J to deter questions, you must submit this form and the sup the supplemental form is attached. If you answer excluded from permit requirements; see Section	nlemental fro	om listed in the	parenthesis following the ques	stion. Mark "X" in the	box in the th	ird column if
SPECIFIC QUESTIONS	MAI	RK "X"	SPECIFIC QUES		MAF	₹K "X"
A. Is this facility a publicly owned treatment works	YES NO	ATTACHED	B. Does or will this facility		YÉS NÓ	ATTACHED
which results in a discharge to waters of the U.S.? (FORM.2A)			proposed) include a confeeding operation or production facility which in	ncentrated animal aquatic animal esults in a discharge		
C is this facility which currently results in	16 - 17	18	D. Is this proposal facility (other	than those described	19 20	21
discharges to waters of the U.S. other than those described in A or B above? (FORM 2C)	22 23	₹ 24	in A or B above) which will to waters of the U.S.? (FOR	IM 2D)	25 26	
E. Does or will this facility treat, store, or dispose of hazardous wastes? (FORM 3)			F. Do you or will you inject at the municipal effluent below the containing, within one qualities, underground sources	e lowermost stratum rter mile of the well.		
G. Do you or will you inject at this facility any	28 29	30	(FORM 4) H. Do you or will you inject at the	is facility fluids for	31 32	33
produced water other fluids which are brought to the surface in connection with conventional oil or natural gas production, inject fluids used for enhanced recovery of oil or natural gas, or inject			special processes such as m Frasch process, solution min situ combustion of fossil fuel geothermal energy? (FORM	ing of minerals, in "or recovery of		
fluids for storage of liquid hydrocarbons? (FORM 4)	34 35	36 %			37 38	1 14 14 39 40 1
Is this facility a proposed stationary source which is one of the 28 industrial categories listed.			J. Is this facility a proposed which is NOT one of the 28	3 industrial categories		
in the instructions and which will potentially emit 100 tons per year of any air pollutant regulated under the Clean Air Act and may affect or be			listed in the instructions and emit 250 tons per year	of any air pollutant		
located in an attainment area? (FORM 5)	40 41	42	regulated under the Clean A or be located in an attainment	ent are? (FORM 5)	43 44	45
SKIP Reusens Hydroelectric P	lant				;.	
15 16-29 30	- Carre	\$ 11 . 1 700			69	
IV. FACILITY CONTACT						
A. NAME & TITLE (la	st, first, & title ' & Ecolog	e) lical Resol		ONE (area code & no	233	
Services			. *			to see a see a see Here to see a
V. FACILITY MAILING ADDRESS).a		45 46 48	4951	. 55	
A STREET OR	P.O. BOX	"5 °E				
1 Riverside Plaza					1897 s \$	
15 16 B. CITY OR TOWN			C. STATE D. ZIP COD	E]		
4 Columbus		6 % \$ \cdot	ОН 43215			
VI. FACILITY LOCATION		. 40	41 .42 .47	51 2	<u> </u>	
A. STREET, ROUTE NO. OR OTH	IER SPECIF	IC IDENTIFIE	R [] [] [] [] [] [] [] [] [] [] [] [] []	1 128		
4200 Hydro Street			List is a second			الإساع ال

70

40

D. STATE

VA

E. ZIP CODE | F. COUNTY CODE

24503

Lynchburg

Amherst

6 Ly

B. COUNTY NAME

C. CITY OR TOWN

CONTINUED FROM THE FRONT												
VII. SIC CODES (4-digit, in order of priority)		3. Al F	٠		*****	y +	San San	B. SECO	MD⇔´			
C 4911 (specify)	. 5.5.	Non-ri	7	N		(spec		. D. SEUU	NU C	<u> </u>	<u> 2240 200 200</u>	<u> </u>
Floctric Services			. ~7			N/A						
15 % [0.16 C 1 4] VIV % 5 [2 2 37 2 3 1 8		: 15		19			D. FOUR	ETH 3			7177
C N/A (specify)	· .,i	Ţ.	√7a	N		(spec						
7/2 N/A N/A		ŀ	7	16	19	N/A						
VIII. OPERATOR INFORMATION			.10	10	10	• 1						
A.A.	IAME	Ξ,				J-12.7.		No.	В	l. Is the na	ame listed in	tem
Appalachian Power Company											so the owner	?
. 0			172		w * 3 - 100 1 1 1	1 2 3	57 . 55	34 MHZ (24	55	X YES	i 🗌 NO	
C. STATUS OF OPERATOR (Enter the appropriate letter in	_				"Other," sp	ecify.)	7 N. A.	D. PH		rea code		
F = FEDERAL M = PUBLIC (other than federal or state) S = STATE O = OTHER (specify)	F	₽	(spec	ify)		1	C A	614		716	1233	
R RRIVATE		6					15	16 18		9 21	22 25	丄
School Street or PO BOX	3.		· · · · · ·	Č.		, ,	5. 5.4					
I Riverside Plaza	,								. *			
F. CITY OR TOWN	7	G. S	STATE	\$. V	H. ZIP C	ODE	IY IN	IDIAN LA	AND		er er trock	Ò
Columbus	1-	O			43215			acility local		ndian land	is?	-
3.()	۱. ۱							YES	N			
5 16 40 40 40 40 40 40 40 40 40 40 40 40 40		42	42		47	.51						اخط
A. NPDES (Discharges to Surface Water)		D F	PSD /A	ir Fı	nissions froi	m Prono	sed Sa	urces)				
VA0087114	, с	ŢŢ	8	N		11,11100,			1			
9 N/ 16 17 18 10 10 10 10 10 10 10	. 9		5 17	18	TT TTA NOTE OF			30				
B. UIC (Underground Injection of Fluids	1 '3	1 10	, , ,,		OTHER (specify)			(Spec	ify)	Mr. es	·
C. T. N/A	C		. 8 .	İ		1			1	•		
9 U 15 16 17 18 30	15	1	3 17	18				30	1			
C. RCRA (Hazardous Wastes)		·			OTHER (specify)			(Spec	ify)		
C T I VAD988204210	9		. 8	1								
5 16 17 18 30	15		5 17	18				30	1			
KI. MAP												
Attach to this application a topographic map of the												
show the outline of the facility, the location of e hazardous waste treatment, storage, or disposal f												
rivers and other surface water bodies in the map at									ground	i. moide	ie ali spility	э,
XII. NATURE OF BUSINESS (provide a brief de				20(10	TID, TOT PTO	3100 100						
The Reusens Hydroelectric Plant consists of				lec	tric aene	ratina	units	with a to	otal a	eneratir	na capacit	v
of 12.5 megawatts.		,				· 3			- · · · · · ·		· 5 r · ·	,
· g												
										•		
(III. CERTIFICATION (see instructions)												
I certify under penalty of law that I have personally												
I certify under penalty of law that I have personally all attachments and that, based on my inquiry of t	hose	e per	rsons	ìmn	ediately re	spons	ible for	obtaining	the in	formation	n contained	in
I certify under penalty of law that I have personally all attachments and that, based on my inquiry of t the application, I believe that the information is to	hose rue,	e per acci	rsons irate a	imn and	ediately re complete.	spons	ible for	obtaining	the in	formation	n contained	in
I certify under penalty of law that I have personally all attachments and that, based on my inquiry of t the application, I believe that the information is to submitting false information, including the possibili	hose rue, ty of	e per acci fine	rsons urate a and in	imm and mpr	ediately re complete.	spons	ible for	obtaining	the in are s	formation ignificant	n contained t penalties	in
I certify under penalty of law that I have personally all attachments and that, based on my inquiry of the application, I believe that the information is to submitting false information, including the possibili	hose rue, ty of	e per acci fine SIG	rsons urate a and in NATUI	imm and mpri RE	ediately re complete. sonment.	espons I am	ible for aware	obtaining	the in are s	formation	n contained t penalties	in
I certify under penalty of law that I have personally all attachments and that, based on my inquiry of the application, I believe that the information is to submitting false information, including the possibility. NAME & OFFICIAL TITLE (type or print)	hose rue, ty of	e per acci fine SIG	rsons urate a and in NATUI	imm and mpri RE	ediately re complete. sonment.	espons I am	ible for aware	obtaining	the in are s	formation ignificant	n contained t penalties	in
I certify under penalty of law that I have personally all attachments and that, based on my inquiry of the application, I believe that the information is to submitting false information, including the possibility. NAME & OFFICIAL TITLE (type or print) John M. McManus	hose rue, ty of	e per acci fine SIG	rsons urate a and in NATUI	imm and mpri RE	ediately re complete.	espons I am	ible for aware	obtaining	the in are s	formation ignificant	n contained t penalties	in
all attachments and that, based on my inquiry of the application, I believe that the information is to	hose rue, ty of	e per acci fine SIG	rsons urate a and in NATUI	imm and mpri RE	ediately re complete. sonment.	espons I am	ible for aware	obtaining	the in are s	formation ignificant	n contained t penalties	in

С

Please print or type in the unshaded areas only

EPA I.D. NUMBER (copy from Item 1 of Form 1)

VAD988204210

Form Approved OMB No. 2040-0086 Approval expires 5-31-92

Form 2C **NPDES**

EPA

U.S. ENVIRONMENTAL PROTECTION AGENCY

APPLICATION FOR PERMIT DISCHARGE WASTEWATER EXISTING MANUFACTURING, COMMERCIAL, MINING, AND SILVICULTURAL OPERATIONS

Consolidated Permits Program

OUTFALL LOCATION

For each outfall, list the latitude and longitude of its location to the nearest 15 seconds and the name of the receiving water.

A. OUTFALL NUMBER	В	LATITUDE	4	C.	LONGITITUDE		D. RECEIVING WATER (name)	
(list)	(list) 1. DEG 2. MIN 3. SEC 1. DEG 2. MIN 3. SEC	3. SEC						
001	37	27	50	79	11	08	James River	
002	37	27	50	79	11	08	James River	
003	37	27	50	79	11	08	James River	
004	37	27	50	79	11	08	James River	
005	37	27	50	79	11	08	James River	
		E SIG	120					

II. FLOWS, SOURCES OF POLLUTION, AND TREATMENT TECHNOLOGIES

A. Attach a line drawing showing the water flow through the facility. Indicate sources of intake water, operations contributing wastewater to the effluent, treatment units labeled to correspond to the more detailed descriptions in Item B. Construct a water balance on the line drawing by showing average flows between intakes, operations, treatment units, and outfalls. If a water balance cannot be determined (e.g., for certain mining activities), provide a pictorial description of the nature and amount of any sources of water and any collection or treatment measures. See Figure 2

B. For each outfall, provide a description of: (1) All operations contributing wastewater to the effluent, including process wastewater, sanitary wastewater, cooling water, and storm water runoff, (2) The average flow contributed by each operation, and (3) The treatment received by the wastewater. Continue on additional sheets

a. OPERATION (list)	b. AVERAGE	2. OPERATION(S) CONTRIBUTING FLOW										
	(INCLUDE U		a. DESCRIPTION	b. LIST CODES FROM								
Unit 1 Intermediate Guide			Discharge to surface waters	4-A								
Bearing	0.025	MGD										
Max. Flow	0.025	MGD										
Unit 2 Intermediate Guide			Discharge to surface waters	4-A								
Bearing	0.025	MGD										
Max. Flow	0.025	MGD										
Unit 3 Intermediate Guide			Discharge to surface waters	4-A								
Bearing	0.025	MGD										
Max. Flow	0.025	MGD										
Unit 4 Intermediate Guide			Discharge to surface waters	4-A								
Bearing	0.0144	MGD										
Max. Flow	0.0216	MGD										
Unit 5 Intermediate Guide			Discharge to surface waters	4-A								
Bearing	0.0144	MGD										
Max. Flow	0.0216	MGD										
	Unit 2 Intermediate Guide Bearing Max. Flow Unit 3 Intermediate Guide Bearing Max. Flow Unit 4 Intermediate Guide Bearing Max. Flow Unit 5 Intermediate Guide Bearing	Unit 2 Intermediate Guide Bearing	Unit 2 Intermediate Guide Bearing Max. Flow Unit 3 Intermediate Guide Bearing Max. Flow Unit 4 Intermediate Guide Bearing Unit 5 Intermediate Guide Bearing Unit 5 Intermediate Guide Bearing Max. Flow Unit 5 Intermediate Guide Bearing Max. Flow Unit 5 Intermediate Guide Bearing Unit 5 Intermediate Guide Bearing O.0144 MGD MGD	Unit 2 Intermediate Guide Bearing Max. Flow Unit 3 Intermediate Guide Bearing Max. Flow Unit 4 Intermediate Guide Bearing Unit 4 Intermediate Guide Bearing Unit 5 Intermediate Guide Bearing Unit 5 Intermediate Guide Bearing Max. Flow Unit 5 Intermediate Guide Bearing Max. Flow Unit 6 Intermediate Guide Bearing Unit 6 Intermediate Guide Discharge to surface waters Discharge to Surface Waters Bearing Unit 6 Intermediate Guide Discharge to Surface Waters Discharge to Surface Waters Discharge to Surface Waters	Unit 2 Intermediate Guide Bearing Max. Flow Unit 3 Intermediate Guide Bearing Max. Flow Unit 4 Intermediate Guide Bearing Max. Flow Unit 5 Intermediate Guide Bearing Max. Flow Unit 5 Intermediate Guide Bearing Max. Flow Unit 5 Intermediate Guide Bearing Max. Flow Unit 6 Intermediate Guide Bearing O.0144 MGD MGD Unit 6 Intermediate Guide Bearing O.0144 MGD MGD Unit 7 Intermediate Guide Bearing O.0144 MGD MGD MGD							

Please print or type in the unshaded areas only

EPA I.D. NUMBER (copy from Item 1 of Form 1) VAD988204210

Form Approved
OMB No. 2040-0086
Approval expires 5-31-92

Form 2C

EPA

U.S. ENVIRONMENTAL PROTECTION AGENCY

APPLICATION FOR PERMIT DISCHARGE WASTEWATER EXISTING MANUFACTURING, COMMERCIAL, MINING, AND SILVICULTURAL OPERATIONS

Consolidated Permits Program

I. OUTFALL LOCATION

NPDES

For each outfall, list the latitude and longitude of its location to the nearest 15 seconds and the name of the receiving water.

A. OUTFALL NUMBER	В	LATITUDE		C.	LONGITITUDE		D. RECEIVING WATER (name)					
(list)	1. DEG	2. MIN	3. SEC	1. DEG	2. MIN	3. SEC						
006	37	27	50	79	11	08	James River					
								200		100		
		ARTES.	100									

II. FLOWS, SOURCES OF POLLUTION, AND TREATMENT TECHNOLOGIES

A. Attach a line drawing showing the water flow through the facility. Indicate sources of intake water, operations contributing wastewater to the effluent, and treatment units labeled to correspond to the more detailed descriptions in Item B. Construct a water balance on the line drawing by showing average flows between intakes, operations, treatment units, and outfalls. If a water balance cannot be determined (e.g., for certain mining activities), provide a pictorial description of the nature and amount of any sources of water and any collection or treatment measures.

See Figure 2.

B. For each outfall, provide a description of: (1) All operations contributing wastewater to the effluent, including process wastewater, sanitary wastewater, cooling water, and storm water runoff, (2) The average flow contributed by each operation; and (3) The treatment received by the wastewater. Continue on additional sheets if necessary.

	2. OPERATION(S) CONTRIBU	JTING FLOW		3. TREATMENT		4 00
1. OUTFALL (list)	a. OPERATION (list)	b. AVERAG		a. DESCRIPTION		DES FROM
006	Sump Overflow	0.036		Discharge to surface waters	4-A	
	Sources:			See Appendix 3, Note 1		
	Units 1,2,3 generator					
	coolers/thrust bearings	0.0432	MGD			
	#1 air compressor	0.046	MGD			
	Units 1,2,3 intermediate					
	bearings	0.075	MGD			
	Total Average Flow	0.030	MGD			
All Property	Max. Flow	0.154	MGD		1	
						2.8
			1 1	国际工程		The N
						PACE.
			No. 10 Per			
Sec.						100
April 1						
		al devices			1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	
		A STATE OF STATE OF				
in citize a					1000	

	on, leaks, or spins, and	e any of the	discharges describ	bed in Items	II-A or B intermit	tent or seasonal?			
Yes (con	nplete the following to	able)			X No (go to Section III)			
	H WAS IN THE REAL PROPERTY.			3. FREQ			4. FLOW		
NUMBER (list)	CONTRIBU	RATION(s) TING FLOV (st)	N	a. DAYS PER WEEK (specify average)	b.MONTHS PER YEAR (specify average)	a. FLOW RATE (in mgd)	b. TOTAL \ (specify wi	th units)	c. DUR- ATION (in days)
N/A III. PRODUCTION									
. Does an effluent gui	ideline limitation pron	mulgated by E	PA under Section	n 304 of the (Clean Water Act	apply to your facility			
Yes (con	mplete Item III-B)				X No (go to	Section (V)			
. Are the limitations in		ent guideline	expressed in term	s of product			E AND LE	N. A. L. T.	75.75
Yes (com	nplete Item III-C)				No (go to	Section IV)			
		o auantitu wh	nich represents as	actual mean		level of production, expres	sed in the terms as	nd units	
sed in the applicable e				actual filea:	surement or your	level of production, expres	see in the terms at	ild units	
		1	. AVERAGE DAI	LY PRODUC	TION			2 45550	
a. QUANTITY PER DA	AY b. UNITS OF N	MEASURE		c OPER	RATION PRODU	JCT, MATERIAL, ETC.		2. AFFEC	
u. QOANTITI I EN DI	D. CHITC CI II	ILLAGOILE		0.0.2.	(spec			(list outfall nu	
N/A									
IV. Improvements Are you now required reatment equipment or	d by any Federal, Sta practices or any other	er environme	ntal programs wh	ich may affec	ct the discharges	or the construction, upgradi described in this application chedule letters, stipulations	on? This includes,		
IV. Improvements Are you now required reatment equipment or	d by any Federal, Sta practices or any other	er environme inistrative or e	ntal programs whenforcement order	ich may affec	ct the discharges	CONTRACTOR OF THE PROPERTY OF	on? This includes, s, court orders, and	l grant	
IV. Improvements Are you now required reatment equipment or ut is not limited to , per	d by any Federal, Sta practices or any other mit conditions, admir	er environme inistrative or e the following t	ntal programs whenforcement order	ich may affects, enforcement	ct the discharges	described in this applications chedule letters, stipulations	on? This includes, s, court orders, and	grant 4. FINAL COI	
IV. Improvements Are you now required reatment equipment or ut is not limited to , per	d by any Federal, State practices or any othermit conditions, admir Yes (complete the OF CONDITION,	er environme inistrative or e the following t	ntal programs whenforcement order	ich may affect rs, enforcement	ct the discharges ent compliance s	described in this applications chedule letters, stipulations	on? This includes, s, court orders, and B)	l grant	

B. OPTIONAL: You may attach additional sheets describing any additional water pollution control programs (or other environmental projects which may affect your discharges) you now have underway or which you plan. Indicate whether each program is now underway or planned, and indicate your actual or planned schedules for construction.

MARK "X" IF DESCRIPTION OF ADDITIONAL CONTROL PROGRAMS IS ATTACHED

CONTINUED FROM PAGE 2

V. INTAKE AND EFFLUENT CHARACTERISTICS

- A, B, & C: See instructions before proceeding Complete one set of tables for each outfall Annotate the outfall number in the space provided NOTE: Tables V-A, V-B, and V-C are included on separate sheets numbered V-1 through V-9.
- D. Use the space below to list any of the pollutants listed in Table 2c-3 of the instructions, which you know or have reason to believe is discharged or may be discharged from any outfall. For every pollutant you list, briefly describe the reasons you believe it to be present and report any analytical data in your possession.

1. POLLUTANT	2. SOURCE	1. POLLUTANT	2. SOURCE
N/A	N/A	N/A	N/A

VI. POTENTIAL DISCHARGES NOT COVERED BY ANALYSIS

is any pollutant listed in Item V-C a substance or a component of a substance which you currently use or manufacture as an intermediate or final product c

byproduct? Yes (list all such pollutants below)

X No (go to Item VI-B)

CONTINUED FROM THE FRONT

to you have any knowledge or reason to believe that a	my biological test for acute or chronic toxicity has	as been i		
			made on any of your discharge	s or on a
eceiving water in relation to your discharge within the I	ast 5 years?			
Yes (identify the test(s) and de	escribe their purpose below)	X N	o (go to Section VIII)	
II. CONTRACT ANALYSIS INFORMATION				
		Diam		0 Note 4
lere any of the analyses reported in Item V performed	by a contract laboratory or consulting firm?	rieasi	e reference Appendix	A, Note 1.
X YES (list the name,	address, and telephone number of, and ploout	ants	NO (go to Section	(X)
	ch such laboratory or firm below)			
A. NAME	B. ADDRESS		C. TELEPHONE	D. POLLUTANTS ANALYZI
			(area code & no.)	(list)
Water Chemistry, Inc.	3404 Aerial Way Drive, S	W	(540) 343-3618	
				BOD ₅
	Roanoke, Virginia 24018			BOD₅ COD
	Roanoke, Virginia 24018			
	Roanoke, Virginia 24018			COD
	Roanoke, Virginia 24018			COD TOC TSS
	Roanoke, Virginia 24018			COD TOC TSS Ammonia
	Roanoke, Virginia 24018			COD TOC TSS Ammonia Oil & Grease
	Roanoke, Virginia 24018			COD TOC TSS Ammonia Oil & Grease pH
	Roanoke, Virginia 24018			COD TOC TSS Ammonia Oil & Grease pH Temperature
	Roanoke, Virginia 24018			COD TOC TSS Ammonia Oil & Grease pH Temperature Total Residual Chlor
	Roanoke, Virginia 24018			COD TOC TSS Ammonia Oil & Grease pH Temperature
	Roanoke, Virginia 24018			COD TOC TSS Ammonia Oil & Grease pH Temperature Total Residual Chlor
	Roanoke, Virginia 24018			COD TOC TSS Ammonia Oil & Grease pH Temperature Total Residual Chlor
	Roanoke, Virginia 24018			COD TOC TSS Ammonia Oil & Grease pH Temperature Total Residual Chlor
	Roanoke, Virginia 24018			COD TOC TSS Ammonia Oil & Grease pH Temperature Total Residual Chlor
	Roanoke, Virginia 24018			COD TOC TSS Ammonia Oil & Grease pH Temperature Total Residual Chlor
				COD TOC TSS Ammonia Oil & Grease pH Temperature Total Residual Chlor Fecal Coliform
certify under penalty of law that this document and all	attachments were prepared under my direction	n or supe	ervision in accordance with a sy	COD TOC TSS Ammonia Oil & Grease pH Temperature Total Residual Chlor Fecal Coliform
certify under penalty of law that this document and all sure that qualified personnel properly gather and ever	attachments were prepared under my direction	n or supe	ervision in accordance with a sy f the person or persons who m	COD TOC TSS Ammonia Oil & Grease pH Temperature Total Residual Chlor Fecal Coliform
certify under penalty of law that this document and all ssure that qualified personnel properly gather and ev- lose persons directly responsible for gathering this in	attachments were prepared under my direction aluate the information submitted. Based on my formation, the information submitted is, to the b	n or supe inquiry o est of my	ervision in accordance with a sy f the person or persons who m y knowledge and belief, true, ac	COD TOC TSS Ammonia Oil & Grease pH Temperature Total Residual Chlor Fecal Coliform
certify under penalty of law that this document and all ssure that qualified personnel properly gather and ev- lose persons directly responsible for gathering this in am aware that there are significant pealties for submi	attachments were prepared under my direction aluate the information submitted. Based on my formation, the information submitted is, to the b	n or supe inquiry o est of my	ervision in accordance with a sy f the person or persons who m y knowledge and belief, true, ac d imprisonment for knowing vic	COD TOC TSS Ammonia Oil & Grease pH Temperature Total Residual Chlor Fecal Coliform
certify under penalty of law that this document and all ssure that qualified personnel properly gather and even nose persons directly responsible for gathering this information amount and the submitted are significant pealties for submit I. NAME & OFFICIAL TITLE (type or print)	attachments were prepared under my direction aluate the information submitted. Based on my formation, the information submitted is, to the b	n or supe inquiry o est of my	ervision in accordance with a sy f the person or persons who m y knowledge and belief, true, ac d imprisonment for knowing vid B. PHONE NO.	COD TOC TSS Ammonia Oil & Grease pH Temperature Total Residual Chlori Fecal Coliform stem designed to anage the system or courate, and complete. olations. (area code & no.)
certify under penalty of law that this document and all ssure that qualified personnel properly gather and evices persons directly responsible for gathering this information among that there are significant pealties for submit a. NAME & OFFICIAL TITLE (type or print) John M. McManus	attachments were prepared under my direction aluate the information submitted. Based on my formation, the information submitted is, to the bitting false information, including the possibility of	n or supe inquiry o est of my	ervision in accordance with a sy f the person or persons who m y knowledge and belief, true, ac d imprisonment for knowing vic	COD TOC TSS Ammonia Oil & Grease pH Temperature Total Residual Chlori Fecal Coliform stem designed to anage the system or courate, and complete. olations. (area code & no.)
certify under penalty of law that this document and all assure that qualified personnel properly gather and evinose persons directly responsible for gathering this into am aware that there are significant pealties for submits. NAME & OFFICIAL TITLE (type or print) John M. McManus Vice President, Environmental Serv	attachments were prepared under my direction aluate the information submitted. Based on my formation, the information submitted is, to the bitting false information, including the possibility of the poss	n or supe inquiry o est of my	ervision in accordance with a sy f the person or persons who m or knowledge and belief, true, ac and imprisonment for knowing vio B. PHONE NO. (614) 71	COD TOC TSS Ammonia Oil & Grease pH Temperature Total Residual Chlori Fecal Coliform stem designed to anage the system or courate, and complete. blations. (area code & no.) 6-1268
certify under penalty of law that this document and all assure that qualified personnel properly gather and evinose persons directly responsible for gathering this into am aware that there are significant pealties for submits. NAME & OFFICIAL TITLE (type or print) John M. McManus Vice President, Environmental Serv	attachments were prepared under my direction aluate the information submitted. Based on my formation, the information submitted is, to the bitting false information, including the possibility of the poss	n or supe inquiry o est of my	ervision in accordance with a sy f the person or persons who m is knowledge and belief, true, ac id imprisonment for knowing vic B. PHONE NO. (614) 71	COD TOC TSS Ammonia Oil & Grease pH Temperature Total Residual Chlori Fecal Coliform stem designed to anage the system or courate, and complete. blations. (area code & no.) 6-1268
	attachments were prepared under my direction aluate the information submitted. Based on my formation, the information submitted is, to the bitting false information, including the possibility of the poss	n or supe inquiry o est of my	ervision in accordance with a sy f the person or persons who m or knowledge and belief, true, ac and imprisonment for knowing vio B. PHONE NO. (614) 71	COD TOC TSS Ammonia Oil & Grease pH Temperature Total Residual Chlori Fecal Coliform stem designed to anage the system or courate, and complete. blations. (area code & no.) 6-1268

OUTFALL NO. V. INTAKE AND EFFLUENT CHARACTERISTICS 001 PART A 4. INTAKE (optional) 3. UNITS 2. EFFLUENT (specify if blank) a. LONG TERM AVRG. VALUE b. No. of 1. POLLUTANT c. LONG TERM AVRG. VALUE d. No. of a. MAXIMUM DAILY VALUE b. MAXIMUM 30 DAY VALUE Analyses Analyses (1) Concentration (2) Mass a. Concentration b. Mass (1) Concentration (1) Concentration (2) Mass 1) Concentration (2) Mass Est.* kg/d <5 1 mg/l < 0.473 <5 a. BOD 12 kg/d 1 Est.* mg/l 14 1.32 b. COD 4.1 mg/l kg/d 1 Est.* 0.407 4.3 c. TOC Est.* kg/d 2 1 0.0946 mg/l 1 d. TSS < 0.2 1 Est.* kg/d <0.2 < 0.0189 mg/l e. Ammonia (as N) 0.025 Est.** MGD VALUE: 0.025 VALUE: VALUE: VALUE: f. Flow °C 18.2 VALUE: 17.6 Est.* VALUE: 4 26.0 VALUE: VALUE: g. Temperature (winter) °C 24.1 Est.* VALUE: 30.7 VALUE: VALUE: h. Temperature (summer) VALUE: Minimum Maximum Minimum Maximum Est.* Standard Units 8.45 6.88 i. pH

PART B		2					100							
	2. Mar	2. Mark 'X' 3. EFFLUENT							4. UN	ITS	5. INTAKE (optional)			
			a. MAXIMUM DA	ILY VALUE	b. MAXIMUM 30	DAY VALUE	c. LONG TERM AVRG. VALUE		Less .	(specify i	f blank)	a. LONG TERM AVRG. VALUE		
1. POLLUTANT	a. Believed	b. Believed Absent	(1) Concentration	(2) Mass	(1) Concentration	(2) Mass	(1) Concentration	(2) Mass	d. No. of Analyses	a. Concentration	b. Mass	(1) Concentration	(2) Mass	d. No. of Analyses
a. Bromide		Х			P 10	1								
b. Chlorine, Tot. Residual		Х	0.16	0.0151	10				4	mg/l	kg/d	0.15		4
c. Color		х	VALUE:	- VA	VALUE:		VALUE:					VALUE:		
d. Fecal Coliform		Х	VALUE:	291	VALUE:		VALUE:	B. Male	1	#/100 mL		VALUE:	548	1
e. Fluoride		Х		11/11/11										
f. Nitrate/Nitrite		Х		The same					They y					

^{*}See Appendix A Note 2

^{**}See Appendix A Note 3

OUTFALL NO. 001 V. INTAKE AND EFFLUENT CHARACTERISTICS PART B (CONTINUED) 5. INTAKE (optional) 4. UNITS 2. Mark 'X' 3. EFFLUENT (specify if blank) a. LONG TERM AVRG. VALUE b. MAXIMUM 30 DAY VALUE c. LONG TERM AVRG. VALUE a. MAXIMUM DAILY VALUE d. No. of Design transport 1. POLLUTANT Analyses Analyses (1) Concentration (2) Mass (2) Mass a. Concentration b. Mass (2) Mass (1) Concentration (2) Mass (1) Concentration X g. TON Est.* kg/d <5.0 1 mg/l X < 0.473 < 5.0 h. O&G X Phosphorus Radioactivity VALUE: VALUE: VALUE: VALUE: (1) Total Alpha X VALUE: VALUE: VALUE: (2) Total Beta X VALUE: VALUE: VALUE: X VALUE: VALUE: (3) Total Radium VALUE: VALUE: X VALUE: VALUE: (4) Radium 226 X k. Sulfate X Sulfide X m. Sulfite X n. Surfactants X o. Aluminum X p. Barium X g. Boron Х . Cobalt X s. Iron X . Magnesium X

u. Molybdenum

v. Manganese

w. Tin x. Titanium X

X

V. INTAKE AND EFF	LUEN	r C	HARACTI	FRISTIC	S								OUTFAL 001	
PART C	LOLIV		IIAIAOII							The same				
TARTO	2. Mar	יצי א			3. EFFLUE	NT			Lebes 7	4. UN	ITS	5. INTAKE (option		ptional)
	Z. Ividi	1	a. MAXIMUM DA	ILY VALUE			c. LONG TERM AVRG. VALUE		1	(specify		a. LONG TERM AVRG. VALUE		
1. POLLUTANT	Required Description	. Believed Absent	(1) Concentration	(2) Mass	(1) Concentration	(2) Mass	(1) Concentration	(2) Mass	d. No. of Analyses	a. Concentration	b. Mass	(1) Concentration	(2) Mass	d. No. o Analyse
METALS, CYANIDE, AND														
1M. Antimony		X	Let 1											
2M. Arsenic		х						Elban.	F-84	W				
3M. Beryllium		Х						1						
4M. Cadmium		Х						A AT	THE PARTY NAMED IN					25
5M. Chromium		Х					of the state of th	607						
6M. Copper		X				10	The state of the s	VA.						
7M. Lead		X				101	TO TO	NA.				11 10 10 10		
8M. Mercury		X				All .	10	V						1000
9M. Nickel		Х				160								
10M. Selenium		Х				No.								
11M. Silver		Х			and the same									
12M. Thallium		X			A TON		4							
13M. Zinc		X		0	W. Le	500m.								1
14M. Cyanide		Х			A STATE OF THE STA							Mark Street		
15M. Phenols		Х		ASSESSE		10								
DIOXIN					The Man	A								724
2,3,7,8-tetrachlorodibenzo-P-diox	tin	X	Describe Resu	ults:	100									

Form 2C Page V-3

V. INTAKE AND EFF	LUE	NT C	HARACTI	ERISTIC	s			VAL	1988204	210			OUTFALI 001	
PART C (CONTINUED)										1	Bull.			
	2.1	Mark 'X'			3. EFFLUE	NT				4. UN		5. 11	NTAKE (or	ptional)
			a. MAXIMUM DA	ILY VALUE	b. MAXIMUM 30	DAY VALUE	c. LONG TERM A	VRG. VALUE	69	(specify i	f blank)	a. LONG TERM AV	RG. VALUE	
1. POLLUTANT	a. Testing Required	Present C. Believed Absent	(1) Concentration	(2) Mass	(1) Concentration	(2) Mass	(1) Concentration	(2) Mass	d. No. of Analyses	a. Concentration	b. Mass	(1) Concentration	(2) Mass	d. No. of Analyses
GC/MS FRACTION VOL	ATIL	E CO	IPOUNDS											
1V. Acrolein		Х												
2V. Acrylonitrile		X								A.				
3V. Benzene		Х							1					
4V. Bis (Chloromethyl) Ether		X			4.76年,pths			1	100					
5V. Bromoform		Х					addition.	0.07						
6V. Carbon Tetrachloride		X				889		The same of				5. 5. 6.		12
7V. Chlorobenzene		X				139						0.00		
8V. Chlorodibromomethane		X				No.		V				VIII - 1 - 2 - 1 - 1		
9V. Chloroethane		X			Parameter San				100					
10V. 2-Chloroethylvinyl Ether		X		a de la companya de l		No.	19							
11V. Chloroform		X			2000 BBS		TO AGY							
12V. Dichlorobromomethane		X	Websie de la				A.		2 11 15					
13V. Dichlorodifluoromethane		X				COLO.								
14V. 1,1-Dichloroethane		X			Cassill	YA					CARSON AVER			
15V. 1,2-Dichloroethane		X		addition.										
16V. 1,1-Dichloroethylene		X				100			1000					
17V. 1,2-Dichloropropane		X			(I)				F 1 10					
18V. 1,3-Dichloropropylene		X	-070006	10	The No.									
19V. Ethylbenzene		X	The state of the s		100							8007675		
20V. Methyl Bromide		X	7 6 7 9 7 9	10/ 10						11 7 144				
21V. Methyl Chloride		X		Y										

V. INTAKE AND EFFL	UEN	тс	HARACT	ERISTIC	s								OUTFALI 001	
PART C (CONTINUED)										1				
7 11 (1 0 (00)(1111022)	2. Ma	rk 'X'			3. EFFLUE	NT				4. UN	ITS	5.1	NTAKE (or	otional)
		1	a. MAXIMUM DA	AILY VALUE	b. MAXIMUM 30		c. LONG TERM A	VRG. VALUE		(specify	if blank)	a. LONG TERM A	/RG. VALUE	Sale and
1. POLLUTANT	Required Selieved	Present Believed Absent	(1) Concentration	(2) Mass	(1) Concentration	(2) Mass	(1) Concentration	(2) Mass	d. No. of Analyses	a. Concentration	b. Mass	(1) Concentration	(2) Mass	d. No. of Analyses
GC/MS FRACTION VOL	ATILE	CON	IPOUNDS	(continued)										
22V. Methylene Chloride		X										2.4 54.5 4 5.		
23V. 1,1,2,2-Tetrachloroethane		X								V				
24V. Tetrachloroethylene		X												
25V. Toluene		Х			Landay ITM									
26V. 1,2-Trans Dichloroethylene		X					A SECTION ASSESSMENT							4
27V. 1,1,1-trichloroethane		X				d	and the same							
28V. 1,1,2-trichloroethane		X												
29V. Trichloroethylene		X						W. T.						7
30V. Trichlorofluoromethane		X												
31V. Vinyl Chloride	100	Х			S. A. S. SAS		1							
GC/MS FRACTION ACID	COM	POU	NDS											
1A. 2-Chlorophenol		X			The same of the sa		9							
2A. 2,4-Dichlorophenol		X				an.	NO.		130					
3A. 2,4-Dimethylphenol		X			The second second			State of the last	De la Re					
4A. 4,6-Dinitro-O-Cresol		X		A2 28 W 16										
5A. 2,4-Dinitrophenol		X			B. Ves					CALL TO SERVE		The second		
6A. 2-Nitrophenol		х		484										
7A. 4-Nitrophenol		х	The Laboratory	- Vince of										
8A. P-Chloro-M-Cresol		X		5. 1	19									
9A. Pentachlorophenol		X							F-19					
10A. Phenol		х		N. Value	13 C 13 Hz 15 H									
11A. 2,4,6-Trichlorophenol		X	10 To 10 To 10											

Page V-5

Form 2C

V. INTAKE AND EFFL	UEN	ТС	HARACT	ERISTIC	s			VAL	988202	1210			OUTFALI 001	
PART C (CONTINUED)	the same									N. Call				
	2. Ma	rk 'X'	100 P. N. A.		3. EFFLUE	NT				4. UN	ITS	5. 11	NTAKE (or	otional)
			a. MAXIMUM DA	ILY VALUE	b. MAXIMUM 30		c. LONG TERM A	VRG. VALUE	100	(specify	if blank)	a. LONG TERM A	RG. VALUE	
1. POLLUTANT	a. Testing Required b. Believed	Present c. Believed Absent	(1) Concentration	(2) Mass	(1) Concentration	(2) Mass	(1) Concentration	(2) Mass	d. No. of Analyses	a. Concentration	b. Mass	(1) Concentration	(2) Mass	d. No. of Analyses
GC/MS FRACTION BASE	/NEU	TRA	L COMPOL	INDS										
1B. Acenaphthene		X							,					
2B. Acenaphtylene		X						(28by		1				
3B. Anthracene		X							lan.					
4B. Benzidine		Х			1000			AF						
5B. Benzo(a)Anthracene		X					(E) (E) (E) (E)							
6B. Benzo(a)Pyrene		X				439		The second						
7B. 3,4-Benzofluoranthene	1	X					The Notes							
8B. Benzo(ghi)perylene		X						Y						
9B. Benzo(k)fluoranthene		X				10				199 6 19 19				
10B. Bis(2-chloroethoxy)methane		X				A PARTY NAMED IN	A 10		100			AND THE REAL PROPERTY.		
11B. Bis(2-chloroethyl)ether		X			APPEN.		10.49							
12B. Bis(2-chloroisopropyl)ether		X			1				3 3					100
13B. Bis(2-ethylhexyl)phthalate		X			No.				F 6					
14B. 4-bromophenyl Phenyl Ether		X	7.			- No			196					
15B. Butyl Benzyl Phthalate		X		ACCEPTANT		1				A Consider			1995	11/2
16B. 2-Chloronaphthalene		X			B B	del								
17B. 4-chlorophenyl Phenyl Ether		X												
18B. Chrysene		X		10										
19B. Dibenzo(a,h)anthracene		Х	April 1	A VID	No.									
20B. 1,2-dichlorobenzene		Х		10 10					No. Page			Street Street		
21B. 1,3-dichlorobenzene	1834	X												101

	A The								79				OUTFAL	
V. INTAKE AND EFFL	LUENT	CI	HARACT	ERISTIC	S					Allen			001	
PART C (CONTINUED)		3.6								100				
	2. Mark	'X'			3. EFFLUE	NT			4	4. UN	ITS	5.1	NTAKE (o	ptional)
			a. MAXIMUM DA	AILY VALUE	b. MAXIMUM 30	DAY VALUE	c. LONG TERM A	VRG. VALUE	100	(specify	if blank)	a. LONG TERM A	VRG. VALUE	
1. POLLUTANT	a. Testing Required b. Believed Present	S. Believed Absent	(1) Concentration	(2) Mass	(1) Concentration	(2) Mass	(1) Concentration	(2) Mass	d. No. of Analyses	a. Concentration	b. Mass	(1) Concentration	(2) Mass	d. No. of Analyses
GC/MS FRACTION BASI	E/NEUT	RA	L COMPOL	JNDS (con	tinued)									
22B. 1,4-dichlorobenzene		Х												
23B. 3,3-dichlorobenzidine		Х						Tito.	Sp. 5-)	4				
24B. diethylphthalate		Х							No					
25B. Dimethylphthalate		Х		Kent dan			The state of the s	A AT	1					
26B. di-N-Butylphthalate		Х					- CONTROL	00						100
27B. 2,4-Dinitrotoluene	9 3	Х			200	10		10						
28B. 2,6-dinitrotoluene		Х				100								
29B. di-N-Octyl Phthalate		Х				- VA		Y	178.5					
30B. 1,2-Diphenylhydrazine		Х												13.5
31B. Fluoranthene		Х		19 20 - 19		N. N.			100				W. J. J.	
32B. Fluorene		Х			1985 May 1		100							
33B. Hexachlorobenzene		Х		19.0357	1		-				172			
34B. Hexachlorobutadiene		Х			图 是	1970a				A STATE OF				
35B. Hexachlorocyclopentadiene		Х			Vibratile .	No.								-
36B. Hexachloroethane		Х		ASSESSED										
37B. Indeno(1,2,3-cd)Pyrene		Х			TO VOL	400							10.00	
38B. Isophorone		Х		M								15 10 10 1		
39B. Naphthalene	100	Х		60					15.000					
40B. Nitrobenzene		Х	Married Williams	A VA	M									
41B. N-Nitrosodimethylamine		Х		10 1	The state of the s									
42B. N-Nitrosodi-N-Propylamine		х	100	NA.										

								VAL	988204	210			OUTFALI	NO
V. INTAKE AND EFF	LUF	NT C	HARACTI	ERISTIC	s								001	
PART C (CONTINUED)						The state				The same	Die.			
PART C (CONTINUED)	12	Mark 'X'			3. EFFLUE	NT				4. UN	ITS	5.1	NTAKE (o)	ptional)
	2.	Wark A	a. MAXIMUM DA	LY VALUE	b. MAXIMUM 30		c. LONG TERM A	VRG. VALUE	100	(specify	if blank)	a. LONG TERM A	VRG. VALUE	Towns.
1. POLLUTANT	a. Testing Required	b. Believed Present c. Believed Absent	(1) Concentration		(1) Concentration	(2) Mass	(1) Concentration	(2) Mass	d. No. of Analyses	a. Concentration	b. Mass	(1) Concentration	(2) Mass	d. No. o Analyse
GC/MS FRACTION BAS	SE/NE	UTRA	L COMPOU	NDS (con	tinued)									
43B. N-Nitrosodiphenylamine		X					-							
44B. Phenanthrene		X					100			No.				
45B. Pyrene		X					British British	79000	No.					
46B. 1,2,4-trichlorobenzene		X												
GC/MS FRACTION PES	STICI	DES												
1P. Aldrin		X		yn.		109		The same of						
2P. a-BHC		X				111	100	19	138					
3P. b-BHC		X				No.								
4P. g-BHC		X				10	100							
5P. d-BHC		X	1000000			-							BOOM TO SE	
6P. Chlordane		X			407700		100						A CONTRACTOR	
7P. 4,4-DDT		X			100	Balabian,	-		1000000					
8P. 4,4-DDE		X			B. Ba	State .								
9P. 4,4-DDD		X			The same of the sa									
10P. Dieldrin		X		ANDER					1000000					
11P. a-Endosulfan		X		M	TO TO	100	TERRO BANK							
12P. b-Endosulfan		X		WA.					100					
13P. Endosulfan sulfate		X	-	No.									8 98 98 98	
14P. Endrin	1	X	1	A VA										
15P. Endrin Aldehyde		X	- 個	100				13,000						
16P. Heptachlor		X		M			4 14 5 4							

V. INTAKE AND EF	FLUENT C	HARACT	ERISTIC	S					A			OUTFALL 001	
PART C (CONTINUED)		4 4 1								Wax.			
TART C (CONTINUED)	2. Mark 'X'	+		3. EFFLUE	NT				4. UN	ITS	5.1	NTAKE (or	ptional)
	Z. Mark A	a. MAXIMUM DA	ILY VALUE	b. MAXIMUM 30		c. LONG TERM A	VRG. VALUE	107	(specify	if blank)	a. LONG TERM A	VRG. VALUE	
1. POLLUTANT	a. Testing Required b. Believed Present c. Believed Absent	(1) Concentration	(2) Mass	(1) Concentration	(2) Mass	(1) Concentration	(2) Mass	d. No. of Analyses	a. Concentration	b. Mass	(1) Concentration	(2) Mass	d. No. of Analyses
GC/MS FRACTION PE		ontinued)											
17P. Heptachlor Epoxide	X	, and a				4							
18P. PCB-1242	X							1000					
19P. PCB-1254	X	The Paragraph						No.			No. 3		
20P. PCB-1221	X			wik?			N MI					100	
21P. PCB-1232	X					BONNE CONTRACTOR				The Air			
22P. PCB-1248	X				1		NA.	11.30					
23P. PCB-1260	X				11/1/		No.				No. Chief of		
24P. PCB-1016	X					100	4						
25P. Toxaphene	X												

EP	A I	D.	NU	MB	ER
VA	DS	88	20	42	10

OUTFALL NO. V. INTAKE AND EFFLUENT CHARACTERISTICS 002 PARTA 4. INTAKE (optional) 3. UNITS 2. EFFLUENT (specify if blank) a. LONG TERM AVRG. VALUE b. No. of d. No. of C. LONG TERM AVRG. VALUE 1. POLLUTANT a. MAXIMUM DAILY VALUE b. MAXIMUM 30 DAY VALUE Analyses Analyses (1) Concentration a. Concentration b. Mass (2) Mass (1) Concentration (2) Mass (1) Concentration (2) Mass 1) Concentration kg/d <5 mg/l Est.* <5 < 0.473 a. BOD 12 1 Est.* mg/l kg/d 1.32 14 b. COD 4.1 1 kg/d 0.407 Est.* mg/l 4.3 c. TOC Est.* kg/d 2 1 mg/l 0.0946 1 d. TSS < 0.2 1 Est.* mg/l kg/d < 0.2 < 0.0189 e. Ammonia (as N) 0.025 MGD VALUE: Est.** 0.025 VALUE: VALUE: VALUE: f. Flow °C 18.2 4 VALUE: 17.6 Est.* 26.0 VALUE: VALUE: VALUE: g. Temperature (winter) Est.* °C 24.1 VALUE: 30.7 VALUE: VALUE: VALUE: h. Temperature (summer) Minimum Maximum Minimum Maximum Standard Units Est.* 8.45 6.88 i. pH

PART B	2. Ma	rk 'Y'			3. EFFLUE	NT	1			4. UN	ITS	5. 11	NTAKE (o	ptional)
	2. 1910	1	a. MAXIMUM DA	ILY VALUE	b, MAXIMUM 30		c. LONG TERM A	VRG. VALUE		(specify i	f blank)	a. LONG TERM A	VRG. VALUE	20
1. POLLUTANT	a. Believed	Present b. Believed Absent	(1) Concentration	(2) Mass	(1) Concentration	(2) Mass	(1) Concentration	(2) Mass	d. No. of Analyses	a. Concentration	b. Mass	(1) Concentration	(2) Mass	d. No. o Analyse
a. Bromide		Х			B B	d								
b. Chlorine, Tot. Residual		X	0.16	0.0151	1				4	mg/l	kg/d	0.15		4
c. Color	W////	X	VALUE:	100	VALUE:		VALUE:					VALUE:		
d. Fecal Coliform		X	VALUE:	291	VALUE:		VALUE:		1	#/100 mL	P. Halling	VALUE:	548	1
e. Fluoride		Х		10 1		TO PAGE	BACK REA							
f. Nitrate/Nitrite		Х					40 100		100-23		DAY.			

^{*}See Appendix A Note 2

^{**}See Appendix A Note 3

<u>EPA I.D. NUMBER</u> VAD988204210

OUTFALL NO. 002 V. INTAKE AND EFFLUENT CHARACTERISTICS PART B (CONTINUED) 4. UNITS 5. INTAKE (optional) 3. EFFLUENT 2. Mark 'X' (specify if blank) a. LONG TERM AVRG. VALUE b. MAXIMUM 30 DAY VALUE c. LONG TERM AVRG. VALUE a. MAXIMUM DAILY VALUE d. No. of d. No. of 1. POLLUTANT Analyses Analyses (1) Concentration (2) Mass (2) Mass (1) Concentration (2) Mass a. Concentration b. Mass (2) Mass (1) Concentration (1) Concentration g. TON mg/l kg/d <5.0 1 X <5.0 < 0.473 Est.* h. O&G X Phosphorus Radioactivity VALUE: VALUE: VALUE: (1) Total Alpha VALUE: VALUE: VALUE: VALUE: VALUE: (2) Total Beta VALUE: VALUE: VALUE: VALUE: (3) Total Radium VALUE: VALUE: VALUE: VALUE: (4) Radium 226 k. Sulfate X X Sulfide X m. Sulfite X n. Surfactants X o. Aluminum X p. Barium X Boron X Cobalt X s. Iron X Magnesium X u. Molybdenum v. Manganese X w. Tin X x. Titanium

V. INTAKE AND EFF PART C		0.0							1 2 4 1	WA WAR				
PARTO	2. Mark	ıvı			3. EFFLUE	NT				4. UN	ITS	5, 11	NTAKE (or	otional)
	Z. Mari	^	a. MAXIMUM DA	ILY VALUE	b. MAXIMUM 30		c. LONG TERM A	VRG. VALUE		(specify		a. LONG TERM AV		T
1. POLLUTANT	a. Testing Required . Believed Present	. Believed Absent	1) Concentration		(1) Concentration	(2) Mass	(1) Concentration	(2) Mass	d. No. of Analyses	a. Concentration	b. Mass	(1) Concentration	(2) Mass	d. No. o Analyse
METALS, CYANIDE, AND														
1M. Antimony		х												
2M. Arsenic		Х						Box.		V			No. of the St.	
3M. Beryllium		х							bo.					
4M. Cadmium		х						A ST	100					
5M. Chromium		х					USECTION.	0.09						
6M. Copper		х				400								
7M. Lead		х				1000		W.						
8M. Mercury		х					V	Y						
9M. Nickel		Х								The state of		W		
10M. Selenium		х					N 100							
11M. Silver		Х			A10000		1000							
12M. Thallium		Х												
13M. Zinc		Х							95 96					
14M. Cyanide		Х			* Transfer	N								
15M. Phenols		х		ASTER										

V. INTAKE AND EFF	LUEN	тс	HARACTI	ERISTIC	s			VAL	1988204	Allen			OUTFALI 002	
PART C (CONTINUED)										1	lin.			
,,,,,,	2. Mai	k 'X'			3. EFFLUE	NT				4. UN	ITS	5. 11	NTAKE (or	ptional)
	1	T	a. MAXIMUM DA	ILY VALUE	b. MAXIMUM 30		c. LONG TERM A	VRG. VALUE	1	(specify	if blank)	a. LONG TERM AV	RG. VALUE	
1. POLLUTANT	a. Testing Required b. Believed	c. Believed Absent	(1) Concentration	(2) Mass	(1) Concentration	(2) Mass	(1) Concentration	(2) Mass	d. No. of Analyses	a. Concentration	b. Mass	(1) Concentration	(2) Mass	d. No. of Analyses
GC/MS FRACTION VOI														
1V. Acrolein		Х							No. of the last					
2V. Acrylonitrile		X		KA TE			100	Eller .		4				
3V. Benzene		X						- Melley						
4V. Bis (Chloromethyl) Ether		Х					The second second	N 10	- Com-					
5V. Bromoform	10 10	Х					MEDION.	100						
6V. Carbon Tetrachloride		Х				S		M						
7V. Chlorobenzene		X	G.				N. A.							
8V. Chlorodibromomethane		Х				10	Company No.	N. A.						
9V. Chloroethane		X				10	189							
10V. 2-Chloroethylvinyl Ether		X					1							
11V. Chloroform		X			acceptions.		100							
12V. Dichlorobromomethane		Х			1		-							
13V. Dichlorodifluoromethane		Х			N E	Elle.								
14V. 1,1-Dichloroethane		X			The state of the s	M								
15V. 1,2-Dichloroethane		X		ASSESSED	、但				100					
16V. 1,1-Dichloroethylene		X			W. VA	19	165 - 165							
17V. 1,2-Dichloropropane		X			10							100000000000000000000000000000000000000		
18V. 1,3-Dichloropropylene	1	X	-000bs	V				A COL						
19V. Ethylbenzene		X	A STATE OF THE STA	A VOL	100		60 CT 6 CT 8							
20V. Methyl Bromide		X		AND A				100						
21V. Methyl Chloride		X												1

V. INTAKE AND EFFL	UEI	NT C	HARACT	ERISTIC	s			VAL	J98820 ²	72 10			OUTFALI 002	
PART C (CONTINUED)														
	2. M	ark 'X'		4 - 1	3. EFFLUE	NT				4. UN	ITS	5. 11	NTAKE (or	ptional)
			a. MAXIMUM DA	AILY VALUE	b. MAXIMUM 30		c. LONG TERM A	VRG. VALUE	100	(specify	if blank)	a. LONG TERM AV	/RG. VALUE	
1. POLLUTANT	a. Testing Required	Present c. Believed Absent	(1) Concentration	(2) Mass	(1) Concentration	(2) Mass	(1) Concentration	(2) Mass	d. No. of Analyses	a. Concentration	b. Mass	(1) Concentration	(2) Mass	d. No. of Analyses
GC/MS FRACTION VOL			POUNDS	(continued)										
22V. Methylene Chloride		X												
23V. 1,1,2,2-Tetrachloroethane		Х												
24V. Tetrachloroethylene		X						1	Dan.					
25V. Toluene		Х						N. M.	1					
26V. 1,2-Trans Dichloroethylene		X					diffica							
27V. 1,1,1-trichloroethane		X				1		Vis.						
28V. 1,1,2-trichloroethane		X				11	No.							
29V. Trichloroethylene		X			DE CONTRACTOR	A		-V						
30V. Trichlorofluoromethane		X				10								
31V. Vinyl Chloride		X				-	109							
GC/MS FRACTION ACID	CON	IPOU	NDS											
1A. 2-Chlorophenol		X			9									
2A. 2,4-Dichlorophenol		X				500						15 . 199.5		
3A. 2,4-Dimethylphenol		X			No. of	THE			1 6					
4A. 4,6-Dinitro-O-Cresol		X		400000										
5A. 2,4-Dinitrophenol		X			The War	10								
6A. 2-Nitrophenol		X				,								
7A. 4-Nitrophenol		X	all states	100						7				
8A. P-Chloro-M-Cresol		X	- Comment	No.				14						
9A. Pentachlorophenol		X		1										
10A. Phenol		Х		V		197, 460								
11A. 2,4,6-Trichlorophenol		X	B. Ville									1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1		

								VAL	988204	210			OUTERL	NO
W INTAKE AND SEEL		NTO	HABACT	EDICTIO									OUTFALL 002	
V. INTAKE AND EFFL	UE	NIC	HARACI	EKISTIC	,3					400			002	
PART C (CONTINUED)										W. william	Day .			100
	2. N	lark 'X'			3. EFFLUE				4	4. UN			NTAKE (op	itional)
			a. MAXIMUM DA	ILY VALUE	b. MAXIMUM 30	DAY VALUE	c. LONG TERM A	VRG. VALUE	d. No. of	(specify	if blank)	a. LONG TERM AV	RG. VALUE	d. No. of
1. POLLUTANT	a Testing Required	Present C. Believed	(1) Concentration	(2) Mass	(1) Concentration	(2) Mass	(1) Concentration	(2) Mass	Analyses	a. Concentration	b. Mass	(1) Concentration	(2) Mass	Analyses
GC/MS FRACTION BASE	/NE	UTRA	L COMPOL	INDS										
1B. Acenaphthene		X							1					
2B. Acenaphtylene		X					199	Ellin.			The Court			
3B. Anthracene		X					1					10 P.A.P. S		100
4B. Benzidine		X						N AT	THE P	HT 200	367			
5B. Benzo(a)Anthracene		X					1603730kg	69	ME Y					
6B. Benzo(a)Pyrene		X				69	Demonstration of the last of t	Vita III						
7B. 3,4-Benzofluoranthene		X				19		The same						
8B. Benzo(ghi)perylene		X			7.49	ANY.		V						
9B. Benzo(k)fluoranthene		X			testo de la composición della	AP	题							
10B. Bis(2-chloroethoxy)methane		X					19							
11B. Bis(2-chloroethyl)ether		X			405000		10.67							
12B. Bis(2-chloroisopropyl)ether		X	Marie L.		1									
13B. Bis(2-ethylhexyl)phthalate		X				200								
14B. 4-bromophenyl Phenyl Ether		X			The state of the s									
15B. Butyl Benzyl Phthalate		X		400000		100								
16B. 2-Chloronaphthalene		X				All I								100
17B. 4-chlorophenyl Phenyl Ether		X					LAVARA I							
18B. Chrysene		X		WA										200
19B. Dibenzo(a,h)anthracene		X	A Partie	D 100		LT TANK		BEET L						
20B. 1,2-dichlorobenzene		X		10 1										
21B. 1,3-dichlorobenzene		X								68 E 48				

Form 2C Page V-6

V. INTAKE AND EFFL	UE	NT C	HARACT	ERISTIC	cs				J9662U ²	Allen			OUTFALI 002	
PART C (CONTINUED)		100								1	lan.			
	12. N	ark 'X			3. EFFLUE	NT				4. UN	ITS	5.1	NTAKE (or	ptional)
			a. MAXIMUM DA	ILY VALUE	b. MAXIMUM 30		c. LONG TERM A	VRG. VALUE	137	(specify	if blank)	a. LONG TERM A	/RG. VALUE	
1. POLLUTANT	a. Testing Required	a. Testing Required b. Believed Present c. Believed	(1) Concentration	(2) Mass	(1) Concentration	(2) Mass	(1) Concentration	(2) Mass	d. No. of Analyses	a. Concentration	b. Mass	(1) Concentration	(2) Mass	d. No. of Analyses
GC/MS FRACTION BASE	E/NE	UTRA	L COMPOL	INDS (cor	ntinued)									
22B. 1,4-dichlorobenzene		X												
23B. 3,3-dichlorobenzidine		X			F 10 10			an-		4				
24B. diethylphthalate		X					- W		5 100					100
25B. Dimethylphthalate		X						A ME						
26B. di-N-Butylphthalate	100	X					e statement	9.07						
27B. 2,4-Dinitrotoluene		X				100		The same						
28B. 2,6-dinitrotoluene		X				B	10							
29B. di-N-Octyl Phthalate		X				- CA	The second second	Y						
30B. 1,2-Diphenylhydrazine		X			N. E. P. L.									
31B. Fluoranthene		X					1							
32B. Fluorene		X			40000									
33B. Hexachlorobenzene		X			1		V							
34B. Hexachlorobutadiene		X				Sign.								
35B. Hexachlorocyclopentadiene		X			Carrier .									
36B. Hexachloroethane		X		48880										
37B. Indeno(1,2,3-cd)Pyrene		X												
38B. Isophorone		X										St. A. T. St. Att.		
39B. Naphthalene		X	4 .min	Wh.	No.		A. A.							
40B. Nitrobenzene		X			Jan 19 miles									
41B. N-Nitrosodimethylamine		Х		X	The second second		BERTHE .							
42B. N-Nitrosodi-N-Propylamine		X		The same				Maja di kata	Man di	La Manie	Service in the	Country of		

Page V-7

V. INTAKE AND EFF	LUENT	CI	HARACTI	ERISTIC	s			VAL	0988204	210			OUTFALL 002	
PART C (CONTINUED)				5. 1255							No.		La gradi	
Truct & (continued)	2. Mari	'X'			3. EFFLUE	NT				4. UN	ITS	5. 11	NTAKE (or	ptional)
	2. 10.01.		a. MAXIMUM DA	ILY VALUE	b. MAXIMUM 30		c. LONG TERM A	VRG. VALUE	100	(specify	if blank)	a. LONG TERM AV	RG. VALUE	
1. POLLUTANT	a. Testing Required b. Believed Present	c. Believed Absent	(1) Concentration	(2) Mass	(1) Concentration	(2) Mass	(1) Concentration	(2) Mass	d. No. of Analyses	a. Concentration	b. Mass	(1) Concentration	(2) Mass	d. No. of Analyses
GC/MS FRACTION BAS	SE/NEUT	RAI	L COMPOU	INDS (con	tinued)									
43B. N-Nitrosodiphenylamine		х												
44B. Phenanthrene		х						Str.		W				
45B. Pyrene		X						-	3	Balley 200				
46B. 1,2,4-trichlorobenzene		Х					No.							
GC/MS FRACTION PES	STICIDES	3												
1P. Aldrin		X				49	-	M						
2P. a-BHC		Х				All		100						
3P. b-BHC		Х				18		Y						
4P. g-BHC		Х												
5P. d-BHC		х					D 10							
6P. Chlordane		X				SA	1							
7P. 4,4-DDT		Х					W							
8P. 4,4-DDE		Х				88%.			1000					1
9P. 4,4-DDD		X			Versuit?	10								
10P. Dieldrin		х		ANDERS					1000					
11P. a-Endosulfan		X				All								
12P. b-Endosulfan		Х		MA TO S			N. 450 10 10					914 9586 9		44.7
13P. Endosulfan sulfate		Х	-	NA.	1							100000000000000000000000000000000000000		
14P. Endrin		х	- April	N. Ya.	10				1					
15P. Endrin Aldehyde		Х		10 1	Company of the Compan									
16P. Heptachlor		х		VIA					1					

V. INTAKE AND EF	FLUEN	T C	HARACTI	ERISTIC	cs					Allen			OUTFALI 002	
PART C (CONTINUED)			20 10 10 10											
	2. Ma	rk 'X'			3. EFFLUE	NT			1	4. UN	ITS	5.1	NTAKE (or	ptional)
			a. MAXIMUM DA	ILY VALUE	b. MAXIMUM 30		c. LONG TERM A	VRG. VALUE	100	(specify	if blank)	a. LONG TERM A	VRG. VALUE	
1. POLLUTANT	a. Testing Required	Present c. Believed Absent	(1) Concentration	(2) Mass	(1) Concentration	(2) Mass	(1) Concentration	(2) Mass	d. No. of Analyses	a. Concentration	b. Mass	(1) Concentration	(2) Mass	d. No. of Analyses
GC/MS FRACTION PE	STICIDE	S (c)	ontinued)											
17P. Heptachlor Epoxide		X												
18P. PCB-1242		X								4				
19P. PCB-1254		Х							100					
20P. PCB-1221		Х						M	1					
21P. PCB-1232		X					690 mg							
22P. PCB-1248		Х				109							100	1
23P. PCB-1260		X				All								
24P. PCB-1016		Х				A		Y						-
25P. Toxaphene		Х				No.								

EPA	I.D.	NUN	ABER	1
VAD	988	3204	1210	1

OUTFALL NO. V. INTAKE AND EFFLUENT CHARACTERISTICS 003 PART A 4. INTAKE (optional) 2. EFFLUENT 3. UNITS (specify if blank) a. LONG TERM AVRG. VALUE 1. POLLUTANT c. LONG TERM AVRG. VALUE d. No. of b. No. of b. MAXIMUM 30 DAY VALUE a. MAXIMUM DAILY VALUE Analyses b. Mass (1) Concentration a. Concentration (1) Concentration (2) Mass 1) Concentration (2) Mass (1) Concentration (2) Mass kg/d <5 < 0.473 Est.* mg/l 1 a. BOD <5 12 kg/d Est.* mg/l 1 14 1.32 b. COD kg/d 4.3 0.407 Est.* mg/l 4.1 c. TOC 2 1 0.0946 Est.* kg/d mg/l d. TSS 1 < 0.2 Est.* mg/l kg/d 1 < 0.0189 < 0.2 e. Ammonia (as N) 0.025 MGD VALUE: 0.025 Est.** VALUE: VALUE: VALUE: f. Flow Est.* 18.2 °C 4 26.0 17.6 VALUE: VALUE: VALUE: g. Temperature (winter) VALUE: 24.1 °C Est.* VALUE: 30.7 VALUE: h. Temperature (summer) VALUE: VALUE: Minimum Maximum Minimum Maximum Standard Units 6.88 Est.* 8.45 i. pH

PART B	2. Mark	'X'			3. EFFLUE	NT				4. UN	ITS	5. 11	NTAKE (o	ptional)
1. POLLUTANT			a. MAXIMUM DA	ILY VALUE	b. MAXIMUM 30	DAY VALUE	c. LONG TERM A	VRG. VALUE		(specify i	f blank)	a. LONG TERM A	VRG. VALUE	
	a. Believed Present	Absent Absent	(1) Concentration	(2) Mass	(1) Concentration	(2) Mass	(1) Concentration	(2) Mass	d. No. of Analyses	a. Concentration	b. Mass	(1) Concentration	(2) Mass	d. No. of Analyses
a. Bromide		Х		M.	B 6									
b. Chlorine, Tot. Residual		X	0.16	0.0151					4	mg/l	kg/d	0.15		4
c. Color		Х	VALUE:		VALUE:		VALUE:					VALUE:		MARKET
d. Fecal Coliform		X	VALUE:	291	VALUE:		VALUE:		1	#/100 mL		VALUE:	548	1
e. Fluoride		Х		10										
f. Nitrate/Nitrite		X		10										

^{*}See Appendix A Note 2

^{**}See Appendix A Note 3

OUTFALL NO. V. INTAKE AND EFFLUENT CHARACTERISTICS 003 PART B (CONTINUED) 5. INTAKE (optional) 4. UNITS 3. EFFLUENT 2. Mark 'X' (specify if blank) a. LONG TERM AVRG. VALUE b. MAXIMUM 30 DAY VALUE c. LONG TERM AVRG. VALUE a. MAXIMUM DAILY VALUE d. No. of d. No. of 1. POLLUTANT Analyses Analyses (1) Concentration (2) Mass (2) Mass a. Concentration b. Mass (2) Mass (1) Concentration (1) Concentration (2) Mass (1) Concentration g. TON kg/d < 5.0 1 < 0.473 Est.* mg/l <5.0 X h. O&G X Phosphorus . Radioactivity VALUE: VALUE: VALUE: VALUE: (1) Total Alpha VALUE: VALUE: VALUE: VALUE: (2) Total Beta VALUE: VALUE: VALUE: VALUE: (3) Total Radium VALUE: VALUE: X VALUE: VALUE: (4) Radium 226 k. Sulfate X X Sulfide X m. Sulfite X n. Surfactants X o. Aluminum X p. Barium X q. Boron X Cobalt X s. Iron X t. Magnesium X u. Molybdenum X v. Manganese X w. Tin X x. Titanium

Form 2C Page V-2

V. INTAKE AND EF	FLUENT	СН	ARACTE	ERISTIC	s					Allen			OUTFAL 003	
PART C										100				
7,11,110	2. Mark	'X'			3. EFFLUE	NT				4. UN	IITS	5. 1	NTAKE (o	otional)
			a. MAXIMUM DAI	LY VALUE	b. MAXIMUM 30		c. LONG TERM A	VRG. VALUE	100	(specify	if blank)	a. LONG TERM A	/RG. VALUE	
1. POLLUTANT	a. Testing Required b. Believed Present	Absent (1)) Concentration	(2) Mass	(1) Concentration	(2) Mass	(1) Concentration	(2) Mass	d. No. of Analyses	a. Concentration	b. Mass	(1) Concentration	(2) Mass	d. No. o Analyse
METALS, CYANIDE, AN	D TOTAL	PHE	NOLS											
1M. Antimony		X	#5.00	Branch and					1					
2M. Arsenic		Х					100		FR.	W				200
3M. Beryllium		X					The second							10000
4M. Cadmium		х						M	1					
5M. Chromium		Х			A		190000	801	181 18 3					5.5
6M. Copper		Х				M		NA.						
7M. Lead		X				109		-	1				E1184 14.7	
8M. Mercury		Х				10		V						
9M. Nickel		Х				N/A	All All							-
10M. Selenium		Х					1	1000						
11M. Silver		Х			- COM		100	1000						
12M. Thallium		Х			9		-							
13M. Zinc		Х			M Ra					STEEL STEEL				-
14M. Cyanide		Х			All and a second	M								-
15M. Phenois		X		ATTO		N.								
DIOXIN	170.0				The Marie	all I				at at				
2,3,7,8-tetrachlorodibenzo-P-die	oxin	XD	escribe Resu	ults:	A Tomas							ALEXA NET		

V. INTAKE AND EFF	LUE	NT C	HARACTI	ERISTIC	s		* / *		J9882U ²	Allen			OUTFALI 003	
PART C (CONTINUED)		\$100			Market W	Name of the				P. Common	Boom			
	2. N	lark 'X'			3. EFFLUE	NT			A	4. UN	ITS	5. 1	NTAKE (or	otional)
			a. MAXIMUM DA	LY VALUE	b. MAXIMUM 30		c. LONG TERM A	VRG. VALUE	49	(specify	if blank)	a. LONG TERM A	RG. VALUE	
1. POLLUTANT	a. Testing Required	D. Believed Present c. Believed Absent	(1) Concentration	(2) Mass	(1) Concentration (2) Mass		(1) Concentration	(2) Mass	d. No. of Analyses	a. Concentration	b. Mass	(1) Concentration	(2) Mass	d. No. of Analyse
GC/MS FRACTION VOI	ATIL	E CON	IPOUNDS											
1V. Acrolein		Х												
2V. Acrylonitrile		X						Ditta.		4		1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1		
3V. Benzene		X						7 6 10	36					
4V. Bis (Chloromethyl) Ether		X								Shark of				
5V. Bromoform		X					of Ships	1969		Telephone Co.		A SHELL		
6V. Carbon Tetrachloride		X				119		- 100						
7V. Chlorobenzene		Х				ANT		VA						
8V. Chlorodibromomethane		X		J. A.		NA.				Province Code		Est Call		
9V. Chloroethane		X				100								10000
10V. 2-Chloroethylvinyl Ether		X		No. of the last			10							30.00
11V. Chloroform		X			-17550m		No. of Parties							
12V. Dichlorobromomethane		X			1		-							
13V. Dichlorodifluoromethane		X						Her Land						
14V. 1,1-Dichloroethane	1 20	X			The same of the sa	TO .				1000				
15V. 1,2-Dichloroethane		X		450000					7200					
16V. 1,1-Dichloroethylene		X		No.	A Com	100		A STATE OF THE STA						
17V. 1,2-Dichloropropane		X			ANY -			Mar (in)						1900
18V. 1,3-Dichloropropylene		Х		A.										1000
19V. Ethylbenzene		X	Married Williams	h Wh	H		the F		1000					
20V. Methyl Bromide		X		100										
21V. Methyl Chloride		х	W.											

V. INTAKE AND EFFL	UE	ENT	CI	HARACT	ERISTIC	s				<u> </u>	Aliena .			OUTFAL 003	
PART C (CONTINUED)															
	2.	Mark '	X,			3. EFFLUE	NT			-	4. UN	ITS	5. II	NTAKE (o	ptional)
		T	1	a. MAXIMUM DA	ILY VALUE	b. MAXIMUM 30	DAY VALUE	c. LONG TERM A	VRG. VALUE	697	(specify	if blank)	a. LONG TERM A	RG. VALUE	
1. POLLUTANT	a. Testing	b. Believed Present c. Believed	Absent	(1) Concentration	(2) Mass	(1) Concentration	(2) Mass	(1) Concentration	(2) Mass	d. No. of Analyses	a. Concentration	b. Mass	(1) Concentration	(2) Mass	d. No. of Analyses
GC/MS FRACTION VOL			OM		(continued)										
22V. Methylene Chloride			x												
23V. 1,1,2,2-Tetrachloroethane			x												147
24V. Tetrachloroethylene			x					- 10							
25V. Toluene			x						A						
26V. 1,2-Trans Dichloroethylene			x					1000 San	807						100
27V. 1,1,1-trichloroethane			x				49		V						
28V. 1,1,2-trichloroethane			x				All	The state of	TO TO			T PART SE			
29V. Trichloroethylene			x				ALL STATES	V	A						
30V. Trichlorofluoromethane			x				. AP				1				
31V. Vinyl Chloride			x				1	100	***************************************						
GC/MS FRACTION ACID	CC	OMPC	U	NDS											
1A. 2-Chlorophenol			X			A CONTRACTOR OF THE PARTY OF TH									
2A. 2,4-Dichlorophenol			X			M. Ha						1000			
3A. 2,4-Dimethylphenol			X			Was of	M			1000					
4A. 4,6-Dinitro-O-Cresol			X	,	A8385	图 图	月								1000
5A. 2,4-Dinitrophenol			X			B B	All								
6A. 2-Nitrophenol			х		10							SPA LINE			
7A. 4-Nitrophenol			X	_ar889a_		183									
8A. P-Chloro-M-Cresol			X	AP-N	the Marie					100					
9A. Pentachlorophenol			X		100									No. 11 Sept.	
10A. Phenol			х		No.					20 11 11					
11A. 2,4,6-Trichlorophenol		100	x	B Ch	删				de la company						

Form 2C Page V-5

V INTAKE AND EEEL	. INTAKE AND EFFLUENT CHARACTERISTICS													
PART C (CONTINUED)	.ULIV	TOTA	INACIE	NOTIC	0					-			003	
TART & (CONTINUED)	2. Ma	'k 'Y'			3. EFFLUE	NT	The second of			4. UN	ITS	5.1	NTAKE (or	ptional)
	Z. IVIC		MAXIMUM DAIL	YVALUE	b. MAXIMUM 30		c. LONG TERM A	VRG. VALUE	W	(specify		a. LONG TERM A		
1. POLLUTANT	a Testing Required b. Believed	C. Believed Absent	oncentration	(2) Mass	(1) Concentration	(2) Mass	(1) Concentration	(2) Mass	d. No. of Analyses	a. Concentration	b. Mass	(1) Concentration	(2) Mass	d. No. o Analyse
GC/MS FRACTION BASE				IDS										
1B. Acenaphthene		X												10000
2B. Acenaphtylene		X										F 285 E		
3B. Anthracene		X		(Applied										
4B. Benzidine		X	17277						The second		Mark Control			
5B. Benzo(a)Anthracene		X					BORDING.	2007	44.00					
6B. Benzo(a)Pyrene		X				19								
7B. 3,4-Benzofluoranthene		X				189	The state of the s	M						-
8B. Benzo(ghi)perylene		X				NOV.	100	4						
9B. Benzo(k)fluoranthene		X				160								
10B. Bis(2-chloroethoxy)methane		X	计图 4				IN AT	,						N. Cal
11B. Bis(2-chloroethyl)ether		X			4455590									-
12B. Bis(2-chloroisopropyl)ether		X			A VA				1					
13B. Bis(2-ethylhexyl)phthalate		X				Elle.								
14B. 4-bromophenyl Phenyl Ether		X			The state of the s	19					March Company			
15B. Butyl Benzyl Phthalate		X	2012	ASSESSE		題		Part of the second						
16B. 2-Chloronaphthalene		X			A W	19		The sales	200			9 9 9 10		
17B. 4-chlorophenyl Phenyl Ether		X			1									
18B. Chrysene	2 1	X	10000	VA	W.				15.68					
19B. Dibenzo(a,h)anthracene		X	A CO	V AS										
20B. 1,2-dichlorobenzene		X		1										
21B. 1,3-dichlorobenzene		X	FA	TO.				-55		194 5 5				

V. INTAKE AND EFFL	LUEN.	ТС	HARACTI	ERISTIC	s			VAL	J9882U ²	1210			OUTFALI 003	
PART C (CONTINUED)		The same								No.				
171111 0 (0011111010)	2. Mar	k 'X'		A SMARK	3. EFFLUE	NT				4. UN	ITS	5. 1	NTAKE (or	ptional)
	2. 11101	T	a. MAXIMUM DA	ILY VALUE	b. MAXIMUM 30		c. LONG TERM A	VRG. VALUE	100	(specify	if blank)	a. LONG TERM AV	/RG. VALUE	
1. POLLUTANT	Required b. Believed	c. Believed Absent	(1) Concentration	(2) Mass	(1) Concentration	(2) Mass	(1) Concentration	(2) Mass	d. No. of Analyses	a. Concentration	b. Mass	(1) Concentration	(2) Mass	d. No. of Analyses
GC/MS FRACTION BASI	E/NEU	TRA	L COMPOU	NDS (con	tinued)									
22B. 1,4-dichlorobenzene		X												100
23B. 3,3-dichlorobenzidine		Х						0		- Co.				
24B. diethylphthalate		X							No.					
25B. Dimethylphthalate		Х					No.	A POP	1					
26B. di-N-Butylphthalate	1 1 1	X			1		15707h							
27B. 2,4-Dinitrotoluene		X				10		M						
28B. 2,6-dinitrotoluene		X				All	M	-						
29B. di-N-Octyl Phthalate		X				10		V	1					
30B. 1,2-Diphenylhydrazine		X				10				Sec.				
31B. Fluoranthene		X									Street of the			
32B. Fluorene		X			A10090a		1000							
33B. Hexachlorobenzene		X			1		V							
34B. Hexachlorobutadiene		Х			M. Re	Bbs.						1000000000		
35B. Hexachlorocyclopentadiene		X			The state of the s	T	Barrier San							
36B. Hexachloroethane		X	7.3	45000					1000					
37B. Indeno(1,2,3-cd)Pyrene		Х		1	TON YOU	19							200000	
38B. Isophorone		Х		The second	-									-
39B. Naphthalene		Х	artitles.											
40B. Nitrobenzene		X	- And	A VO	19					Mark State of				
41B. N-Nitrosodimethylamine		X		10	NO.									
42B. N-Nitrosodi-N-Propylamine		X	The same of the sa	10										

								VAL	988204	210	2 (40) (2) (3) (3)		OUTEAL	NO
		- 01	LADACT	FDICTIO									OUTFALL 003	
V. INTAKE AND EFF	-LUEN	I CI	HARACII	ERISTIC	.5					Allen			003	
PART C (CONTINUED)							The Late of the			10				
	2. Mar	k 'X'			3. EFFLUE				4	4. UN			NTAKE (or	ptional)
			a. MAXIMUM DA	ILY VALUE	b. MAXIMUM 30	DAY VALUE	c. LONG TERM A	VRG. VALUE	d. No. of	(specify	if blank)	a. LONG TERM AV	RG. VALUE	d. No. o
1. POLLUTANT	10 - 0	c. Believed Absent	(1) Concentration	(2) Mass	(1) Concentration	(2) Mass	(1) Concentration	(2) Mass	Analyses	a. Concentration	b. Mass	(1) Concentration	(2) Mass	Analyse
GC/MS FRACTION BA	SE/NEU	ΓRA	L COMPOU	INDS (con	tinued)									
43B. N-Nitrosodiphenylamine		X										7,00		1000
44B. Phenanthrene		X					Eld.			W				
45B. Pyrene		X	24.1						Man.					
46B. 1,2,4-trichlorobenzene		X	Mark Services											
GC/MS FRACTION PES	STICIDE	S												
1P. Aldrin		X				100		The same						3 (5.5)
2P. a-BHC		Х				109	10	No.						
3P. b-BHC		X				NO.	The state of the s							
4P. g-BHC		X						and the second						
5P. d-BHC		X					1							
6P. Chlordane		X			APENDO		100							
7P. 4,4-DDT		X			1									
8P. 4,4-DDE		X			No. No.	Elb.								
9P. 4,4-DDD		X			Vine 1	- W			SCORE N					
10P. Dieldrin		X		ASSESSE								7.31.31.31		
11P. a-Endosulfan		X			10 10 m	1	No. of the last							
12P. b-Endosulfan		Х		N.				Market 1	6786 A					
13P. Endosulfan sulfate		X	4000	M	100			65480° 35						8.4 (1)
14P. Endrin		Х		P AV	No.				-			Section 1		
15P. Endrin Aldehyde		X		10 4						100				-
16P. Heptachlor		X		- M										

V. INTAKE AND EF	FLUENT	СНА	RACTI	ERISTIC	cs					Man			OUTFALI 003	
PART C (CONTINUED)										Ball	No.			
	2. Mark	'X'			3. EFFLUE	NT			ELL ST	4. UN	ITS	5.1	NTAKE (or	ptional)
			AXIMUM DA	ILY VALUE	b. MAXIMUM 30	DAY VALUE	c. LONG TERM A	VRG. VALUE	109	(specify	if blank)	a. LONG TERM A	VRG. VALUE	
1. POLLUTANT	a. Testing Required b. Believed Present	Absent (1)	oncentration	(2) Mass	(1) Concentration	(2) Mass	(1) Concentration	(2) Mass	d. No. of Analyses	a. Concentration	b. Mass	(1) Concentration	(2) Mass	d. No. o Analyse
GC/MS FRACTION PE	STICIDES	(contin	ued)											
17P. Heptachlor Epoxide	100	x				E. William								100
18P. PCB-1242		х								4				100
19P. PCB-1254		х								200 P 400				
20P. PCB-1221		X						M	1					
21P. PCB-1232		х					1070mm	647				E-17-082 T-18	F9	1933
22P. PCB-1248		х	76. 77			100	The state of the s	The same of						BEX. 2
23P. PCB-1260		х				AN I								
24P. PCB-1016		X				10		-						
25P. Toxaphene		х				The same					Acres 1		Call March	

EPA I.D. NUME	BER
VAD9882042	10

OUTFALL NO. V. INTAKE AND EFFLUENT CHARACTERISTICS 004 PART A 4. INTAKE (optional) 2. EFFLUENT 3. UNITS (specify if blank) a. LONG TERM AVRG. VALUE 1. POLLUTANT b. No. of a. MAXIMUM DAILY VALUE b. MAXIMUM 30 DAY VALUE c. LONG TERM AVRG. VALUE d. No. of Analyses Analyses (1) Concentration (1) Concentration (2) Mass a. Concentration b. Mass (1) Concentration (2) Mass (1) Concentration (2) Mass (2) Mass kg/d mg/l <5 <5 < 0.409 Est.* 1 a. BOD 12 12 0.981 Est.* mg/l kg/d 1 b. COD 4.1 Est.* 4.1 1 c. TOC 0.335 mg/l kg/d 0.164 Est.* mg/l kg/d 2 1 2 d. TSS < 0.0164 Est.* < 0.2 e. Ammonia (as N) < 0.2 mg/l kg/d 1 0.0216 0.0216 Est.** MGD VALUE: VALUE: VALUE: f. Flow VALUE: 18.2 °C Est.* VALUE: 18.2 4 g. Temperature (winter) VALUE: VALUE: VALUE: °C VALUE: VALUE: h. Temperature (summer) VALUE: VALUE: Minimum Minimum Maximum Maximum Standard Units 7.5 8.0 Est.* i. pH

PART B	2. Mar	k 'X'			3. EFFLUE	NT	N/			4. UN	ITS	5. II	NTAKE (o	optional)
	***************************************		a. MAXIMUM DA	ILY VALUE	b. MAXIMUM 30	DAY VALUE	c. LONG TERM A	VRG. VALUE	1.6.3	(specify	if blank)	a. LONG TERM A	VRG. VALUE	
1. POLLUTANT	a. Believed	b. Believed Absent	(1) Concentration	(2) Mass	(1) Concentration	(2) Mass	(1) Concentration	(2) Mass	d. No. of Analyses		b. Mass	(1) Concentration	(2) Mass	d. No. of Analyses
a. Bromide		х		7 (4.00)	Car Car	at the same								
b. Chlorine, Tot. Residual		Х	0.23	0.0188					Est.*	mg/l	kg/d	0.15		4
c. Color		х	VALUE:	No.	VALUE:		VALUE:					VALUE:		
d. Fecal Coliform		Х	VALUE:	548	VALUE:		VALUE:		Est.*	#/100 mL		VALUE:	548	1
e. Fluoride		х		1										
f. Nitrate/Nitrite		х		101										

^{*}See Appendix A Note 2

Form 2C Page V-1

^{**}See Appendix A Note 3

OUTFALL NO. 004 V. INTAKE AND EFFLUENT CHARACTERISTICS PART B (CONTINUED) 4. UNITS 5. INTAKE (optional) 3. EFFLUENT 2. Mark 'X' (specify if blank) a. LONG TERM AVRG. VALUE c. LONG TERM AVRG. VALUE b. MAXIMUM 30 DAY VALUE a. MAXIMUM DAILY VALUE d. No. of d. No. of 1. POLLUTANT Analyses Analyses (1) Concentration (2) Mass (2) Mass a. Concentration b. Mass (1) Concentration (2) Mass (1) Concentration (2) Mass (1) Concentration g. TON <5.0 kg/d 1 X < 0.409 Est.* mg/l < 5.0 n. O&G X Phosphorus Radioactivity VALUE: VALUE: VALUE: VALUE: (1) Total Alpha X VALUE: VALUE: VALUE: (2) Total Beta X VALUE: VALUE: VALUE: VALUE: X VALUE: (3) Total Radium VALUE: VALUE: X VALUE: VALUE: (4) Radium 226 Х k. Sulfate X Sulfide X m. Sulfite X n. Surfactants X o. Aluminum X p. Barium X q. Boron X r. Cobalt X s. Iron X t. Magnesium X u. Molybdenum v. Manganese X X w. Tin X x. Titanium

V. INTAKE AND EFFL	UE	NT C	HARACT	ERISTIC	s								OUTFALI 004	
PART C										Real	S .			
174(1)	2 1	lark 'X		A Const	3. EFFLUE	NT				4. UN	ITS	5.1	NTAKE (or	ptional)
			a. MAXIMUM DA	ILY VALUE	b. MAXIMUM 30		c. LONG TERM A	VRG. VALUE	100	(specify	if blank)	a. LONG TERM A	VRG. VALUE	7 1
1. POLLUTANT	a. Testing Required	Present C. Believed	(1) Concentration	(2) Mass	(1) Concentration	(2) Mass	(1) Concentration	(2) Mass	d. No. of Analyses	a. Concentration	b. Mass	(1) Concentration	(2) Mass	d. No.
METALS, CYANIDE, AND														
1M. Antimony		X												
2M. Arsenic		X					65			A				
3M. Beryllium		X					No.	THE REAL PROPERTY.	0					
4M. Cadmium		X					The state of the s	L ST	450					
5M. Chromium		Х					ESTERNA .	100						
6M. Copper		X				100	The state of the s	NA.						
7M. Lead		X				09		The second						
8M. Mercury		X				167	With the second	V					N. H. L. C.	
9M. Nickel		X				100	18							
10M. Selenium		Х					A 19			100 000				
11M. Silver		X			20000m									
12M. Thallium		X			A CONTRACTOR OF THE PARTY OF TH				0.98.91					
13M. Zinc		Х	18. 19.6		图 是	Ch.								1
14M. Cyanide		X			VI SUNT	M						35.00		
15M. Phenols		X												
DIOXIN					W W	All								
2,3,7,8-tetrachlorodibenzo-P-dioxir		X	Describe Res	ults:	No.	200								

V. INTAKE AND EFF	LUEN	T CI	HARACTE	RISTIC	s			VAL	0988204	A			OUTFALI 004	
PART C (CONTINUED)		EE W								1	line			
	2. Mai	k 'X'		Albert Tig	3. EFFLUE	NT			A .	4. UN	ITS	5. II	NTAKE (or	otional)
			a. MAXIMUM DAI	LY VALUE	b. MAXIMUM 30		c. LONG TERM A	VRG. VALUE	139	(specify	if blank)	a. LONG TERM AV	RG. VALUE	
1. POLLUTANT	a. Testing Required b. Believed	c. Believed Absent	(1) Concentration	(2) Mass	(1) Concentration	(2) Mass	(1) Concentration	(2) Mass	d. No. of Analyses	a. Concentration	b. Mass	(1) Concentration	(2) Mass	d. No. of Analyses
GC/MS FRACTION VOI	ATILE	CON	IPOUNDS											
1V. Acrolein		Х					-		1					186
2V. Acrylonitrile		X							E. Carlot	V				100
3V. Benzene		X												
4V. Bis (Chloromethyl) Ether		Х						N AF	A COMPA					
5V. Bromoform		X			P 25 4		05500As.	0.07						
6V. Carbon Tetrachloride		X				AP	The same of the sa	M						
7V. Chlorobenzene		X				109	The state of the s	My.						
8V. Chlorodibromomethane		X				- All		V	100					
9V. Chloroethane		Х				- VO	100							10.3
10V. 2-Chloroethylvinyl Ether		X			PER PER		1							
11V. Chloroform		Х			4570		100							
12V. Dichlorobromomethane		X			A STATE OF THE PARTY OF THE PAR									100
13V. Dichlorodifluoromethane	140	Х			图 是	(B)	Black La							
14V. 1,1-Dichloroethane		X			The state of the s	TO						3.0		16.00
15V. 1,2-Dichloroethane		X		A SERVICE DE		100								
16V. 1,1-Dichloroethylene		X			B 10	M								1
17V. 1,2-Dichloropropane		X		N.								NAME AND A		
18V. 1,3-Dichloropropylene	A RIVE	Х	45000	M							10.73			
19V. Ethylbenzene	8 1 1	X	- Marine	AV A					1 2 1					
20V. Methyl Bromide		Х		10 1										
21V. Methyl Chloride		X	1	M								Mary Control		

V. INTAKE AND EFFL	UE	NT C	HARA	CTERIST	ics			VA	J988204	210			OUTFAL 004	
PART C (CONTINUED)										A CONTRACTOR	ine.			
	2.1	Mark 'X	1		3. EFFLUE	NT				4. UN	ITS	5. 1	NTAKE (o	ptional)
	1.00	75.1		IUM DAILY VALUE	b. MAXIMUM 3	DAY VALUE	c. LONG TERM A	VRG. VALUE	100	(specify	if blank)	a. LONG TERM A	RG. VALUE	
1. POLLUTANT	a. Testing Required	b. Believed Present c. Believed	(1) Concen	tration (2) Mass	s (1) Concentration	(2) Mass	(1) Concentration	(2) Mass	d. No. of Analyses	a. Concentration	b. Mass	(1) Concentration	(2) Mass	d. No. of Analyses
GC/MS FRACTION VOL	ATIL	E CO			d)	WIIIIIIIII								
22V. Methylene Chloride		X												
23V. 1,1,2,2-Tetrachloroethane		X						State of the state		A				
24V. Tetrachloroethylene		X					100					75		
25V. Toluene		X						M	THE STATE OF THE S	No. 1			STI SATE	
26V. 1,2-Trans Dichloroethylene	100	X					+ 1963 P.Co.	0.97						Mark Co.
27V. 1,1,1-trichloroethane		X	1			AS		W.						
28V. 1,1,2-trichloroethane		X				100		No.						L March
29V. Trichloroethylene		X						Y						100
30V. Trichlorofluoromethane		X												
31V. Vinyl Chloride		Х				No.	1							
GC/MS FRACTION ACID	CO	MPO	JNDS											
1A. 2-Chlorophenol		X	Section 1		A									
2A. 2,4-Dichlorophenol		Х				Eta.								
3A. 2,4-Dimethylphenol		X		MES COLUMN		TO								
4A. 4,6-Dinitro-O-Cresol		X		40,85	Be. Salar									
5A. 2,4-Dinitrophenol		X			All All	1								
6A. 2-Nitrophenol		X				Mar.								15000
7A. 4-Nitrophenol		X		W.	WIND WAR									
8A. P-Chloro-M-Cresol	MA	X	500	- C 10		100								
9A. Pentachlorophenol		X	機	The same										
10A. Phenol		Х	TO THE							A				
11A. 2,4,6-Trichlorophenol		X	A 46					100 E						

Page V-5

V. INTAKE AND EFFL	UEN	тс	HARACT	ERISTIC	s					4			OUTFALL 004	
PART C (CONTINUED)					1.00				N 192.3	The same of	Die.		- Table 1	
THE CONTINUES	2. Ma	rk 'X'			3. EFFLUE	NT		1000		4. UN	ITS	5.1	NTAKE (op	otional)
			a. MAXIMUM DA	ILY VALUE	b. MAXIMUM 30		c. LONG TERM A	VRG. VALUE	100	(specify	if blank)	a. LONG TERM A	VRG. VALUE	0.74
1. POLLUTANT	a. Testing Required b. Believed	Present c. Believed Absent	(1) Concentration	(2) Mass	(1) Concentration	(2) Mass	(1) Concentration	(2) Mass	d. No. of Analyses	a. Concentration	b. Mass	(1) Concentration	(2) Mass	d, No. o Analyse
GC/MS FRACTION BASE	NEU	TRA		INDS										
1B. Acenaphthene		Х												
2B. Acenaphtylene		Х							1000	4				
3B. Anthracene		Х							line.	国业企业 在			NAME OF	
4B. Benzidine		Х			10 mg 20 mg	C HELD	11.	N AT	1					
5B. Benzo(a)Anthracene		X					45050m	9.07						
6B. Benzo(a)Pyrene		X				1	and the same	M.						
7B. 3,4-Benzofluoranthene		X				10	1							10000
8B. Benzo(ghi)perylene		Х				Alle		V						
9B. Benzo(k)fluoranthene		X				- AN				ALL SHOULD				
10B. Bis(2-chloroethoxy)methane		X				N. Company	19							1
11B. Bis(2-chloroethyl)ether		X			40000m.		100 m							
12B. Bis(2-chloroisopropyl)ether		X			1		-		100					
13B. Bis(2-ethylhexyl)phthalate		X			图 是	Ela.								
14B. 4-bromophenyl Phenyl Ether		Х				10						6.72 63		
15B. Butyl Benzyl Phthalate		X		A THE REAL PROPERTY.		10								
16B. 2-Chloronaphthalene		Х			A 10-	1								
17B, 4-chlorophenyl Phenyl Ether		Х		10	1									
18B. Chrysene		Х		A. A					Ph. 1216	E (1986)				
19B. Dibenzo(a,h)anthracene		Х	1	AV A	19									
20B. 1,2-dichlorobenzene		Х		10 1									78 S 2 P S	
21B. 1,3-dichlorobenzene		X		10										

Form 2C Page V-6

V. INTAKE AND EFFL	UE	NT (CHARACT	ERISTIC	cs			V/ (L	J9882U ²	Allen.			OUTFALI 004	
PART C (CONTINUED)		1746									War.			
7 11 5 (00///11022)	12.1	Mark ')	c		3. EFFLUE	NT				4. UN	ITS	5. 11	NTAKE (or	ptional)
	-		a. MAXIMUM D	AILY VALUE	b. MAXIMUM 30		c. LONG TERM A	VRG. VALUE	689	(specify	if blank)	a. LONG TERM A	/RG. VALUE	
1. POLLUTANT	a. Testing Required	b. Believed Present c. Believed	Appendix (1) Concentration	(2) Mass	(1) Concentration	(2) Mass	(1) Concentration	(2) Mass	d. No. of Analyses	a. Concentration	b. Mass	(1) Concentration	(2) Mass	d. No. of Analyses
GC/MS FRACTION BASI	E/NE	UTR	AL COMPO	JNDS (cor	ntinued)									
22B. 1,4-dichlorobenzene)	(1					
23B. 3,3-dichlorobenzidine)	(Man.		A				
24B. diethylphthalate	1)	(9					
25B. Dimethylphthalate	100)	(ESCHOOL A	A AT	1					
26B. di-N-Butylphthalate)	(100000s.c.	0.00						
27B. 2,4-Dinitrotoluene	1)	(100		TA .						
28B. 2,6-dinitrotoluene)	(10	10	10		PACE FLA				
29B. di-N-Octyl Phthalate)	(ASP.	Yes	· V						
30B. 1,2-Diphenylhydrazine)	(TO .	100							1
31B. Fluoranthene)	(722,611		-	10							
32B. Fluorene			(Latin.		No.67							
33B. Hexachlorobenzene)	(
34B. Hexachlorobutadiene)	(3.30	图 是	Store .								100
35B. Hexachlorocyclopentadiene)	(Vision P	- M								
36B. Hexachloroethane)	(ART PA		10			150					
37B. Indeno(1,2,3-cd)Pyrene)	(THE WALL	All I								
38B. Isophorone)	(1 3 3					
39B. Naphthalene)	C COMMA	VA	The second			1						100
40B. Nitrobenzene)	(D 60					1					10.00
41B. N-Nitrosodimethylamine)	(100	A STORY	13.66	TO THE REAL	200					E 187	N SHOP
42B. N-Nitrosodi-N-Propylamine)	(The second										9 10 10

Form 2C Page V-7

THE RESERVE OF THE PROPERTY OF THE PERSON OF	No. of the last of						VAL	900204	+210			OUTFAL	I NO
V. INTAKE AND EFF	LUENT	CHARACT	ERISTIC	cs								004	
PART C (CONTINUED)									1	Dian.			
	2. Mark "	x·	4 100	3. EFFLUE	NT			de	4. UN	ITS	5.1	NTAKE (0	ptional)
		a. MAXIMUM D		b. MAXIMUM 30	DAY VALUE	c. LONG TERM A	VRG. VALUE	100	(specify	if blank)	a. LONG TERM A	VRG. VALUE	
1. POLLUTANT	a. Testing Required b. Believed Present c. Believed	Yese (1) Concentration	(2) Mass	(1) Concentration	(2) Mass	(1) Concentration	(2) Mass	d. No. of Analyses	a. Concentration	b. Mass	(1) Concentration	(2) Mass	d. No. of Analyses
GC/MS FRACTION BAS	SE/NEUTR	AL COMPO	UNDS (con										
43B. N-Nitrosodiphenylamine		x						2362					1000
44B. Phenanthrene		X					Plant .						
45B. Pyrene		x											
46B. 1,2,4-trichlorobenzene		x											
GC/MS FRACTION PES	STICIDES												
1P. Aldrin		X			19	The same of the sa							
2P. a-BHC		X			1			95.43					
3P. b-BHC		X			NO.		V						
4P. g-BHC		x			100								
5P. d-BHC		x				1							
6P. Chlordane		x		ACCORD.		No. AF						36.00	
7P. 4,4-DDT		X		19		No.							
8P. 4,4-DDE		X		Mar Mar	Ello.			1					
9P. 4,4-DDD		X		The same of the sa									
10P. Dieldrin		x	450000		100								
11P. a-Endosulfan		x		Ch. Ch.	1								
12P. b-Endosulfan		X		A STATE OF THE PARTY OF THE PAR			100						
13P. Endosulfan sulfate		X				08140345		MANUAL S					
14P. Endrin		x	A WA	M				30.70					
15P. Endrin Aldehyde		x	All and		Part Care								
16P. Heptachlor		x											The Little

V. INTAKE AND EF	FLUEN	IT C	HARACT	ERISTIC	cs					Ann.			OUTFAL 004	
PART C (CONTINUED)										Res .	Dr.			
	2. Ma	ark 'X'			3. EFFLUE	NT				4. UN	ITS	5.1	NTAKE (o	ptional)
			a. MAXIMUM DA	ILY VALUE	b. MAXIMUM 30		c. LONG TERM A	VRG. VALUE	100	(specify	if blank)	a. LONG TERM A	VRG. VALUE	
1. POLLUTANT	a. Testing Required b. Believed	Present c. Believed Absent	(1) Concentration	(2) Mass	(1) Concentration	(2) Mass	(1) Concentration	(2) Mass	d. No. of Analyses	a. Concentration	b. Mass	(1) Concentration	(2) Mass	d. No. o Analyse
GC/MS FRACTION PE	STICIDI	ES (c	ontinued)											
17P. Heptachlor Epoxide	36	X						S. T. A.						
18P. PCB-1242		Х					400			A				
19P. PCB-1254		Х			Transfer and		Va Va		-					
20P. PCB-1221		Х						A ST	1					
21P. PCB-1232		Х					a section and a					F. H.		
22P. PCB-1248		Х				1								
23P. PCB-1260		Х				M	AND THE REAL PROPERTY.				CAR LAR			
24P. PCB-1016		Х				V								
25P. Toxaphene		Х				10	All All							

OUTFALL NO. V. INTAKE AND EFFLUENT CHARACTERISTICS 005 PARTA 4. INTAKE (optional) 3. UNITS 2. EFFLUENT (specify if blank) d. No. of a. LONG TERM AVRG. VALUE b. No. of 1. POLLUTANT b. MAXIMUM 30 DAY VALUE C. LONG TERM AVRG. VALUE a. MAXIMUM DAILY VALUE Analyses Analyses (2) Mass b. Mass (1) Concentration (2) Mass (1) Concentration a. Concentration (2) Mass (1) Concentration (1) Concentration (2) Mass Est.* mg/l kg/d <5 < 0.409 <5 a. BOD 12 Est.* kg/d 1 0.981 mg/l 12 b. COD 4.1 0.335 Est.* mg/l kg/d 1 4.1 c. TOC Est.* kg/d 2 1 0.164 mg/l d. TSS Est.* < 0.0164 kg/d < 0.2 < 0.2 mg/l e. Ammonia (as N) 0.0216 Est.** MGD 0.0216 VALUE: VALUE: VALUE: VALUE: f. Flow 18.2 VALUE: Est.* °C VALUE: 4 18.2 VALUE: g. Temperature (winter) VALUE: °C VALUE: VALUE: VALUE: VALUE: h. Temperature (summer) Minimum Maximum Minimum Maximum Est.* Standard Units 7.5 8.0 i. pH

PART B							The All							
	2. Mark	'X'			3. EFFLUE	NT				4. UN	ITS	5. 11	NTAKE (o	ptional)
			a. MAXIMUM DA	ILY VALUE	b. MAXIMUM 30	DAY VALUE	c. LONG TERM A	VRG. VALUE	277 875	(specify i	if blank)	a. LONG TERM A	VRG. VALUE	
1. POLLUTANT	a. Believed Present	b. Believed Absent	(1) Concentration	(2) Mass	(1) Concentration	(2) Mass	(1) Concentration	(2) Mass	d. No. of Analyses	a. Concentration	b. Mass	(1) Concentration	(2) Mass	d. No. of Analyses
a. Bromide		X			The Man	1								
b. Chlorine, Tot. Residual		Х	0.23	0.0188					Est.*	mg/l	kg/d	0.15		4
c. Color		x	VALUE:	W.	VALUE:		VALUE:					VALUE:		
d. Fecal Coliform		х	VALUE:	548	VALUE:		VALUE:		Est.*	#/100 mL		VALUE:	548	1
e. Fluoride		X		1										
f. Nitrate/Nitrite		X									100	《 篇》。		

^{*}See Appendix A Note 2

^{**}See Appendix A Note 3

OUTFALL NO. V. INTAKE AND EFFLUENT CHARACTERISTICS 005 PART B (CONTINUED) 4. UNITS 5. INTAKE (optional) 2. Mark 'X' 3. EFFLUENT (specify if blank) a. LONG TERM AVRG. VALUE b. MAXIMUM 30 DAY VALUE c. LONG TERM AVRG. VALUE a. MAXIMUM DAILY VALUE d. No. of d. No. of 1. POLLUTANT Analyses Analyses (2) Mass a. Concentration b. Mass (1) Concentration (2) Mass (2) Mass (1) Concentration (2) Mass (1) Concentration (1) Concentration X g. TON kg/d <5.0 <5.0 < 0.409 Est.* mg/l X h. O&G X Phosphorus Radioactivity VALUE: VALUE: VALUE: VALUE: X (1) Total Alpha VALUE VALUE: X VALUE: (2) Total Beta VALUE: VALUE: VALUE: (3) Total Radium X VALUE: VALUE: VALUE: VALUE: VALUE: VALUE: (4) Radium 226 X k. Sulfate X I. Sulfide X m. Sulfite X n. Surfactants X o. Aluminum X p. Barium X Boron X Cobalt . Iron X Magnesium X u. Molybdenum X v. Manganese X w. Tin X x. Titanium

V. INTAKE AND EFF	LUE	NT C	HARACT	ERISTIC	s								OUTFAL 005	
PART C						e sel mai e	A STAN			1900	lbs			
171111	12. M	ark 'X'		Mark State	3. EFFLUE	NT				4. UN	ITS	5.1	NTAKE (o	ptional)
	T		a. MAXIMUM DA	ILY VALUE	b. MAXIMUM 30		c. LONG TERM A	VRG. VALUE	101	(specify	if blank)	a. LONG TERM A	VRG. VALUE	
1. POLLUTANT	Required Relieved	Present Believed Absent	(1) Concentration	(2) Mass	(1) Concentration	(2) Mass	(1) Concentration	(2) Mass	d. No. of Analyses	a. Concentration	b. Mass	(1) Concentration	(2) Mass	d. No. o
METALS, CYANIDE, AND	TOTA	L PH	ENOLS											
1M. Antimony		Х					46							10/13/20
2M. Arsenic		X			12.70 Section		-	Do.		-				
3M. Beryllium		X												
4M. Cadmium		X						1	1					1.73
5M. Chromium		X					A \$1500 Aug.				and the			
6M. Copper		X				10	and the same	10						
7M. Lead		X				M	10	VA.	100					
8M. Mercury		X				10								
9M. Nickel		X				NO.								
10M. Selenium		X	MONEY AND			1	1							
11M. Silver		X			407750		1							1
12M. Thallium		X					4							200
13M. Zinc		X			Mark Mark	Star .	Market Services							100
14M. Cyanide		X			Shorter .	Yes						200		
15M. Phenols		X		Allen		No.			-					Part I
DIOXIN					() () ()	with the same			100					100
2,3,7,8-tetrachlorodibenzo-P-dioxi	in	X	Describe Resi	ults:							Calle Seu	860		

V. INTAKE AND EFF	LUE	NT C	HARACTI	ERISTIC	s			***) 98820 2				OUTFALI 005	
PART C (CONTINUED)										No Marie	litte.			
	2.1	lark 'X'			3. EFFLUE	NT				4. UN	ITS	5. 1	NTAKE (or	otional)
			a. MAXIMUM DA	ILY VALUE	b. MAXIMUM 30		c. LONG TERM A	VRG. VALUE		(specify	if blank)	a. LONG TERM A	RG. VALUE	
1. POLLUTANT	a Testing Required	Present c. Believed Absent	(1) Concentration	(2) Mass	(1) Concentration	(2) Mass	(1) Concentration	(2) Mass	d. No. of Analyses	a. Concentration	b. Mass	(1) Concentration	(2) Mass	d. No. of Analyse
GC/MS FRACTION VOI	LATIL	E CON	/POUNDS											
1V. Acrolein		X												
2V. Acrylonitrile		X							PRINCES!	W. Indian				
3V. Benzene		X					Townson Villa		·					100
4V. Bis (Chloromethyl) Ether		Х					No.	N MY	100					
5V. Bromoform		X					offices.	0.97						
6V. Carbon Tetrachloride		X				10		N					500 N	1000
7V. Chlorobenzene		X				M	AND THE							
8V. Chlorodibromomethane		X		100	MARK TO S	YA	NO.	Y						1863.3
9V. Chloroethane		X											Barrier St.	
10V. 2-Chloroethylvinyl Ether		X					100							
11V. Chloroform		X			445		No.							
12V. Dichlorobromomethane		X			9							1000		
13V. Dichlorodifluoromethane		X			烈 基	Show								
14V. 1,1-Dichloroethane		X			Wheel !			Selection of the						The second
15V. 1,2-Dichloroethane		X		AND THE REAL PROPERTY.	. 題	題								
16V. 1,1-Dichloroethylene		X		M	The Table	100								
17V. 1,2-Dichloropropane		X		M	100		10 TO	27						
18V. 1,3-Dichloropropylene		X		M.						G. 1 4 18				
19V. Ethylbenzene		X	A CONTRACTOR OF THE PARTY OF TH	A YES	No.				7. (8)					0.000
20V. Methyl Bromide		X		10										
21V. Methyl Chloride	317	X	The same	The same of					107					1

														OUTFALL	
V. INTAKE AND EFFL	LUE	ENT	C	HARACT	ERISTIC	S					Altra			005	
PART C (CONTINUED)	9											Manuel			
	2.	Mark	'X'			3. EFFLUE	NT				4. UN	ITS	5.1	NTAKE (op	otional)
				a. MAXIMUM DA	ILY VALUE	b. MAXIMUM 30	DAY VALUE	c. LONG TERM A	VRG. VALUE	69	(specify	f blank)	a. LONG TERM A	VRG. VALUE	
1. POLLUTANT	a. Testing	b. Believed Present	c. Believed Absent	(1) Concentration	(2) Mass	(1) Concentration	(2) Mass	(1) Concentration	(2) Mass	d. No. of Analyses	a. Concentration	b. Mass	(1) Concentration	(2) Mass	d. No. of Analyse
GC/MS FRACTION VOL	ATIL			IPOUNDS	(continued)										
22V. Methylene Chloride			Х												
23V. 1,1,2,2-Tetrachloroethane			Х								A				
24V. Tetrachloroethylene			Х												
25V. Toluene			Х						N APP	40					
26V. 1,2-Trans Dichloroethylene			Х					SPREN.	19.09	104.94					
27V. 1,1,1-trichloroethane			Х				19								
28V. 1,1,2-trichloroethane			Х				M	10	- M						
29V. Trichloroethylene			Х				100	Vo	N.					ERROLL SHI	
30V. Trichlorofluoromethane			Х												STATE OF
31V. Vinyl Chloride			Х				No.	100						***************************************	
GC/MS FRACTION ACID	CC	OMP	OU	NDS											
1A. 2-Chlorophenol			Х			19 1		W							
2A. 2,4-Dichlorophenol			Х			图 观	The .								
3A. 2,4-Dimethylphenol			Х			Short F.	M						TANK BEEN		
4A. 4,6-Dinitro-O-Cresol			Х		ANDERS		题								
5A. 2,4-Dinitrophenol		100	Х			OF BY	1								
6A. 2-Nitrophenol			Х			1									
7A. 4-Nitrophenol			Х		No.		The sales	With the Res							
8A. P-Chloro-M-Cresol			Х	Ar - C	A VA	M					FIRST III				
9A. Pentachlorophenol			Х		10 1	A STATE OF THE PARTY OF THE PAR		B H S D							
10A. Phenol			Х				ME STATE OF							A 17.00	
11A. 2,4,6-Trichlorophenol		di	X	The Ville						Taken S.B.					

								VAL	1988204	+210			OUTFAL	
V. INTAKE AND EFFL	.UEI	NT C	HARACT	ERISTIC	S					do			005	,
PART C (CONTINUED)										The same				
	2. M	ark 'X'			3. EFFLUE	NT				4. UN	ITS	5. 11	NTAKE (or	ptional)
			a. MAXIMUM DA	ILY VALUE	b. MAXIMUM 30	DAY VALUE	c. LONG TERM A	VRG. VALUE	69	(specify	if blank)	a. LONG TERM A	/RG. VALUE	
1. POLLUTANT	a Testing Required	Present C. Believed Absent	(1) Concentration	(2) Mass	(1) Concentration	(2) Mass	(1) Concentration	(2) Mass	d. No. of Analyses	a. Concentration	b. Mass	(1) Concentration	(2) Mass	d. No. of Analyses
GC/MS FRACTION BASE	/NE	UTRA	L COMPOL	INDS										
1B. Acenaphthene		X												
2B. Acenaphtylene		X					(1)	Dr.		4				
3B. Anthracene		Х						- William	line.					1.7.3
4B. Benzidine		X					1	N M						
5B. Benzo(a)Anthracene		Х					e (SCE)	0.07						1870
6B. Benzo(a)Pyrene	П	X				19	The second second	M	L. Carlo					
7B. 3,4-Benzofluoranthene		Х					1	M						100
8B. Benzo(ghi)perylene		Х						Y						
9B. Benzo(k)fluoranthene		X				100								
10B. Bis(2-chloroethoxy)methane		X				-	100					97 157 1181		1000
11B. Bis(2-chloroethyl)ether		X			_000000m		ASP COL	15 (P.)				1 10 - 10		
12B. Bis(2-chloroisopropyl)ether		X						SAR ST						
13B. Bis(2-ethylhexyl)phthalate		X			图 观。									
14B. 4-bromophenyl Phenyl Ether		X					and the second							
15B. Butyl Benzyl Phthalate		X		APPLIED .							1000	1		PER LE
16B. 2-Chloronaphthalene		X				1								No.
17B. 4-chlorophenyl Phenyl Ether		X			10				100					
18B. Chrysene		Х	action.		18									
19B. Dibenzo(a,h)anthracene		X	9	a Va	-M									BOY A
20B. 1,2-dichlorobenzene		Х		10 1	1 91				1.00	J. S. C.				THE STATE OF
21B. 1,3-dichlorobenzene		Х		- VA										

Form 2C Page V-6

									VAL	J98820 ²	+210			OUTFALI	NO.
V. INTAKE AND EFFL	HE	NIT	CI	HARACTI	EDISTIC	2								005	
The second secon	_0_	.141	Ci	IARACTI	LKISTIC	,3					Con.			000	
PART C (CONTINUED)	-				17.4						1 100	ITC	F 11	NTAKE (or	-N
	2.	Mark	,Х,			3. EFFLUE		c. LONG TERM A	VDC VALUE	LAND	4. UN (specify		a. LONG TERM AV		otional)
1. POLLUTANT	a. Testing Required	b. Believed Present	c. Believed Absent	a. MAXIMUM DA (1) Concentration	(2) Mass	b. MAXIMUM 30 (1) Concentration	(2) Mass	(1) Concentration	(2) Mass	d. No. of Analyses	a. Concentration	b. Mass	(1) Concentration	(2) Mass	d. No. o Analyse
GC/MS FRACTION BASI	E/NE	UT	RAI	L COMPOU	INDS (cor	ntinued)									
22B. 1,4-dichlorobenzene			Х								60				
23B. 3,3-dichlorobenzidine			Х						23		-				
24B. diethylphthalate			Х					The second	1						MAL
25B. Dimethylphthalate			Х						M	A COMP			Mary Co.		
26B. di-N-Butylphthalate			X				1777	e eletters.							-
27B. 2,4-Dinitrotoluene			Х				1		The same						
28B. 2,6-dinitrotoluene			Х				1	1	The second						1
29B. di-N-Octyl Phthalate		-	X					Villa Villa	V						
30B. 1,2-Diphenylhydrazine			Х				168	All All							
31B. Fluoranthene			Х					1							
32B. Fluorene		199	X			, e1000ia,		1							
33B. Hexachlorobenzene			X			1									
34B. Hexachlorobutadiene			X				190%								
35B. Hexachlorocyclopentadiene			X				MA					No of Vision			
36B. Hexachloroethane	1		X		A SEEDING										
37B. Indeno(1,2,3-cd)Pyrene			Х				1								
38B. Isophorone			X								F40.55.30				
39B. Naphthalene			Х								N. Carlotte				
40B. Nitrobenzene			X	MA	N 100	19					10.00				
41B. N-Nitrosodimethylamine			Х		NAME										
42B. N-Nitrosodi-N-Propylamine			Х		A.									16 7 16 18	-

								VAL	J988204	1210				
V. INTAKE AND EFF		NT C	HABACTI	EDISTIC	·e								OUTFAL 005	
	LUE	NIC	HARACII	EKISTIC	,3					-			000	
PART C (CONTINUED)										The Line	ITC	F 11	NTAKE (or	-tii)
	2. N	lark 'X'			3. EFFLUE		c. LONG TERM A	VDO VALUE	1.00	4. UN (specify		a. LONG TERM AV		ptional)
1. POLLUTANT	a. Testing Required	Present C. Believed Absent	a. MAXIMUM DA (1) Concentration		(1) Concentration	(2) Mass	(1) Concentration	(2) Mass	d. No. of Analyses	a. Concentration	b. Mass	(1) Concentration	(2) Mass	d. No. o Analyse
GC/MS FRACTION BAS	SE/NE	UTRA	L COMPOU	INDS (con	tinued)									
43B. N-Nitrosodiphenylamine	題しま	X												13.5%
44B. Phenanthrene		X			Strange			The same of		A.				10,000
45B. Pyrene	fil and	X						7000	Ster. I					
46B. 1,2,4-trichlorobenzene		X						1 1						
GC/MS FRACTION PES	STICID	ES												
1P. Aldrin		Х				M		M						
2P. a-BHC		X		4119652		A								
3P. b-BHC		X				- XOV	10	N. A.						
4P. g-BHC		X	张 医原子皮			10	- All			The state of				
5P. d-BHC		X					1							
6P. Chlordane		Х			AND PROCESSION		100							100000
7P. 4,4-DDT		X			A PARTIES		4							
8P. 4,4-DDE		X			M. He	Etc.								
9P. 4,4-DDD		X												
10P. Dieldrin		X		A PRODUCTION OF THE PARTY OF TH		100			4 10 00		18.00			
11P. a-Endosulfan		X			The Aller									
12P. b-Endosulfan		X			1									
13P. Endosulfan sulfate		Х	-400m	M			1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1							
14P. Endrin		X	Married Williams	De Ville	10		PARTY TO							
15P. Endrin Aldehyde		X		10 1										
16P. Heptachlor		X		M							Market No.			

V. INTAKE AND EF	FLUE	NT C	HARACT	ERISTIC	cs					All and a second			OUTFAL 005	
PART C (CONTINUED)		Dist.								1900	No.			
	2. 1	/lark 'X'			3. EFFLUE	NT				4. UN	ITS	5.1	NTAKE (o	ptional)
			a. MAXIMUM DA	ILY VALUE	b. MAXIMUM 30	DAY VALUE	c. LONG TERM A	VRG. VALUE	100	(specify	if blank)	a. LONG TERM A	VRG. VALUE	
1. POLLUTANT	a. Testing Required	Present Present Believed Absent	(1) Concentration	(2) Mass	(1) Concentration	(2) Mass	(1) Concentration	(2) Mass	d. No. of Analyses	a. Concentration	b. Mass	(1) Concentration	(2) Mass	d. No. of
GC/MS FRACTION PE	STICIE	DES (continued)											
17P. Heptachlor Epoxide		X												
18P. PCB-1242	0.0	X								A		200		
19P. PCB-1254		X							Day.	*				
20P. PCB-1221		Х						1 Am						
21P. PCB-1232		X					CONTRACTOR .							100
22P. PCB-1248		Х			120000	1		NA.				SE SECTION		The second
23P. PCB-1260		X				M	1							
24P. PCB-1016		X				N.	No.	W						
25P. Toxaphene		X				1	l list	255						

13

9

22

°C

°C

Standard Units

VALUE:

VALUE:

18.2

4

17.6

24.1

VALUE:

VALUE:

OUTFALL NO. V. INTAKE AND EFFLUENT CHARACTERISTICS 006 PART A 4. INTAKE (optional) 3. UNITS 2. EFFLUENT (specify if blank) a. LONG TERM AVRG. VALUE 1. POLLUTANT a. MAXIMUM DAILY VALUE b. MAXIMUM 30 DAY VALUE c. LONG TERM AVRG. VALUE d. No. of Analyses Analyses (1) Concentration (2) Mass (2) Mass a. Concentration b. Mass (2) Mass (1) Concentration (2) Mass (1) Concentration (1) Concentration kg/d <5 mg/l <8.18 <5 a. BOD 12 kg/d 1 22.9 14 mg/l b. COD kg/d 4.1 1 7.03 4.3 mg/l c. TOC kg/d 2 1 1.64 mg/l d. TSS kg/d < 0.2 1 < 0.2 < 0.327 1 mg/l e. Ammonia (as N) 0.058 0.036 22 MGD VALUE: VALUE: VALUE: VALUE: f. Flow

Maximum

26.0

30.7

8.45

Maximum

VALUE:

VALUE:

Minimum

VALUE:

VALUE:

6.88

Minimum

PART B	2. Mark	'x'			3. EFFLUE	NT				4. UN	ITS	5. 11	NTAKE (o	ptional)
			a. MAXIMUM DA	ILY VALUE	b. MAXIMUM 30	-	c. LONG TERM A	VRG. VALUE		(specify i	f blank)	a. LONG TERM A	RG. VALUE	
1. POLLUTANT	a. Believed Present	bsent	1) Concentration	(2) Mass	(1) Concentration	(2) Mass	(1) Concentration	(2) Mass	d. No. of Analyses	a. Concentration	b. Mass	(1) Concentration	(2) Mass	d. No. of Analyses
a. Bromide		Х			Car Carrie	de la company								
b. Chlorine, Tot. Residual		х	0.16	0.26					4	mg/l	kg/d	0.15		4
c. Color		х	VALUE:	A A	VALUE:		VALUE:					VALUE:		
d. Fecal Coliform		x	VALUE:	291	VALUE:		VALUE:		1	#/100 mL		VALUE:	548	1
e. Fluoride		Х		160 1										
f. Nitrate/Nitrite		X	N/	NA.										

g. Temperature (winter)

i. pH

h. Temperature (summer)

OUTFALL NO. 006 V. INTAKE AND EFFLUENT CHARACTERISTICS PART B (CONTINUED) 5. INTAKE (optional) 4. UNITS 3. EFFLUENT 2. Mark 'X' (specify if blank) a. LONG TERM AVRG. VALUE b. MAXIMUM 30 DAY VALUE c. LONG TERM AVRG. VALUE a. MAXIMUM DAILY VALUE d. No. of Analyses d. No. of 1. POLLUTANT Tuesen Tu Analyses (1) Concentration (2) Mass b. Mass (2) Mass (1) Concentration (2) Mass a. Concentration (2) Mass (1) Concentration g. TON X <5.0 kg/d 1 <8.18 mg/l X <5.0 h. O&G X Phosphorus Radioactivity VALUE: VALUE: VALUE: VALUE: X (1) Total Alpha VALUE: VALUE: X VALUE: VALUE: (2) Total Beta VALUE: VALUE: VALUE: X VALUE: (3) Total Radium VALUE: VALUE: VALUE: (4) Radium 226 VALUE: X k. Sulfate X Sulfide X m. Sulfite X n. Surfactants X o. Aluminum X p. Barium X q. Boron X . Cobalt X s. Iron X . Magnesium X u. Molybdenum X v. Manganese w. Tin X x. Titanium

V INTAKE AND EEE		UT C	NABACTI	EDISTIC	c			VAL	988204	210			OUTFALI 006	
V. INTAKE AND EFFI	UE	AI C	HARACII	EKISTIC	.3				a false	Contract of the second	Man.		000	
PARTO	1 2 M	ark 'X			3. EFFLUE	NT			Alle Jack	4. UN	ITS	5.1	NTAKE (or	otional)
	2. 10	aik A	a. MAXIMUM DA	ILY VALUE	b. MAXIMUM 30		c. LONG TERM A	VRG. VALUE	AN	(specify		a. LONG TERM A	VRG. VALUE	
1. POLLUTANT	a. Testing Required	Present C. Believed	(1) Concentration	(2) Mass	(1) Concentration	(2) Mass	(1) Concentration	(2) Mass	d. No. of Analyses	a. Concentration	b. Mass	(1) Concentration	(2) Mass	d. No. o Analyse
METALS, CYANIDE, AND	TOT	AL PI	HENOLS											
1M. Antimony		X	THE RESIDENCE OF THE PARTY OF T											
2M. Arsenic		X					1			A				
3M. Beryllium		X					1		Dr.					1000
4M. Cadmium		X						1 19	14207		Marine .		10 C 30	
5M. Chromium		X					1900 m	9/9/						
6M. Copper		X				10								21.7%
7M. Lead	1	X				AST	N.	- 10						
8M. Mercury		X				- All	No.	- 7						
9M. Nickel	- 10	X		THE YEAR		All	183				Mary S. S.			
10M. Selenium		X				N	S 19	LW COURS						
11M. Silver		X			2000ba		10.69							10000
12M. Thallium		X			1		N. C.							
13M. Zinc		X			個 点	Silva.						THE REAL PROPERTY.		
14M. Cyanide	100	X		100	No.	M					TH- 50.000 kg			
15M. Phenols		X		ASSESSED		M							15 66 3	
DIOXIN					WA TO	100								
2,3,7,8-tetrachlorodibenzo-P-dioxi	n	X	Describe Resi	ults:	All and									

V. INTAKE AND EFF	LUENT	HARACT	ERISTIC	s				<u> </u>				OUTFALI 006	
PART C (CONTINUED)									1				
	2. Mark 'X			3. EFFLUE	NT				4. UN	ITS	5.1	NTAKE (or	ptional)
		a. MAXIMUM DA	ILY VALUE	b. MAXIMUM 30		c. LONG TERM A	VRG. VALUE	100	(specify	if blank)	a. LONG TERM A	/RG. VALUE	
1. POLLUTANT	a Testing Required b. Believed Present c. Believed	(1) Concentration	(2) Mass	(1) Concentration	(2) Mass	(1) Concentration	(2) Mass	d. No. of Analyses	a. Concentration	b. Mass	(1) Concentration	(2) Mass	d. No. of Analyses
GC/MS FRACTION VOI	LATILE CO	MPOUNDS											
1V. Acrolein	X												
2V. Acrylonitrile	×		TO BY				Direction.	2.000	A				
3V. Benzene	X					N.		Dis.					
4V. Bis (Chloromethyl) Ether	X					No.	NAT	1					1 1 1 1
5V. Bromoform	X					a Million	6.9						
6V. Carbon Tetrachloride	X				1								100
7V. Chlorobenzene	X				107	TO THE							
8V. Chlorodibromomethane	X		Frank King	20 7 7 7 7	10	The second		HE LO			FCC - A		
9V. Chloroethane	X				1/9	100							
10V. 2-Chloroethylvinyl Ether	X				1	1							10000
11V. Chloroform	X	4.1		and the same		No.							
12V. Dichlorobromomethane	X			10		4							1
13V. Dichlorodifluoromethane	X			M. Ma	Illes,	150 p. 130							
14V. 1,1-Dichloroethane	X			Who say	10			13.00					
15V. 1,2-Dichloroethane	X		45000					199					
16V. 1,1-Dichloroethylene	X			The War	19								
17V. 1,2-Dichloropropane	X		M.	10									
18V. 1,3-Dichloropropylene	X	,450 Miles		19									
19V. Ethylbenzene	X	Comment of the same of the sam	A WA	10									8.65
20V. Methyl Bromide	X		10 00										
21V. Methyl Chloride	X		1										

V. INTAKE AND EFFL	UE	NT C	HARACT	ERISTIC	s				J9882U4				OUTFAL 006	
PART C (CONTINUED)			and the same							1	Day.			
T MILE	2. 1	lark 'X			3. EFFLUE	NT			4	4. UN			NTAKE (o	otional)
		1	a. MAXIMUM D	AILY VALUE	b. MAXIMUM 30	DAY VALUE	c. LONG TERM A	VRG. VALUE	100	(specify	if blank)	a. LONG TERM AV	RG. VALUE	
1. POLLUTANT	a. Testing Required	Present C. Believed	(1) Concentration	(2) Mass	(1) Concentration	(2) Mass	(1) Concentration	(2) Mass	d. No. of Analyses	a. Concentration	b. Mass	(1) Concentration	(2) Mass	d. No. of Analyses
GC/MS FRACTION VOL	ATIL	E CO	MPOUNDS	(continued)										
22V. Methylene Chloride		X							1					
23V. 1,1,2,2-Tetrachloroethane		X							ALC: N	V				
24V. Tetrachloroethylene		X							9			REPORTED IN		
25V. Toluene		X						1-18	1					
26V. 1,2-Trans Dichloroethylene		X					stdiction.	0.97	P 4 397					
27V. 1,1,1-trichloroethane		Х				1		The same						122
28V. 1,1,2-trichloroethane		X				14	- The	· W		Harris La				
29V. Trichloroethylene		X				W	30745 SV	V	A Page 1	BASH FA		764		
30V. Trichlorofluoromethane		X				100								
31V. Vinyl Chloride		X					A. A.	***************************************						
GC/MS FRACTION ACID	CO	MPOL	JNDS											
1A. 2-Chlorophenol		X		1	1		4						Barrier.	
2A. 2,4-Dichlorophenol		X												
3A. 2,4-Dimethylphenol		X			Constant of the second	M			185					
4A. 4,6-Dinitro-O-Cresol		X		dillin				a #			BE IN			
5A. 2,4-Dinitrophenol		X			A CO	259							olici. Zebi	
6A. 2-Nitrophenol		X			1						2355 383			
7A. 4-Nitrophenol		X		100										
8A. P-Chloro-M-Cresol		X	Married World	A VA	No.				C. B.					1200
9A. Pentachlorophenol		X		10 1		C. S. A. W.								
10A. Phenol		Х		W										
11A. 2,4,6-Trichlorophenol		X	A VA											1

Form 2C Page V-5


V. INTAKE AND EFFL	UE	NT C	HARACT	ERISTIC	s			VAL)988 <u>20</u> 4	+210			OUTFALI 006	
PART C (CONTINUED)										No.	Hou.			
	2.1	Mark 'X			3. EFFLUE	NT				4. UN	ITS	5. 1	NTAKE (or	otional)
			a. MAXIMUM DA	ILY VALUE	b. MAXIMUM 30	DAY VALUE	c. LONG TERM A	VRG. VALUE	69	(specify	if blank)	a. LONG TERM AV	RG. VALUE	1000
1. POLLUTANT	a. Testing Required	Present c. Believed	(1) Concentration	(2) Mass	(1) Concentration	(2) Mass	(1) Concentration	(2) Mass	d. No. of Analyses	a. Concentration	b. Mass	(1) Concentration	(2) Mass	d. No. of Analyses
GC/MS FRACTION BASE	/NE	UTR/	L COMPOL	INDS										
1B. Acenaphthene		X							1				3 6 2	
2B. Acenaphtylene		X			1.5									1256
3B. Anthracene		X					V	-4000	1		A Property			
4B. Benzidine		X						N AF	· W					
5B. Benzo(a)Anthracene		X					A GENERAL	9.0		Control of the second				100.00
6B. Benzo(a)Pyrene		X				10		N					42	
7B. 3,4-Benzofluoranthene		X			MARKET	All	10	M						
8B. Benzo(ghi)perylene		X				A. A.	Vi Vi							
9B. Benzo(k)fluoranthene		X	10 mg			AD .	周				#25 ST			
10B. Bis(2-chloroethoxy)methane		X				X	1							
11B. Bis(2-chloroethyl)ether	1	X			ACTION.	E 16 A 17 S								
12B. Bis(2-chloroisopropyl)ether		X			1				1		A			
13B. Bis(2-ethylhexyl)phthalate	85	X				ESe.								
14B. 4-bromophenyl Phenyl Ether		X							1000					
15B. Butyl Benzyl Phthalate		Х		4000000			1980							
16B. 2-Chloronaphthalene		X			() ()	1								
17B. 4-chlorophenyl Phenyl Ether		X	Br. Barrell	N.		100								
18B. Chrysene		X	and the same								0			214.65
19B. Dibenzo(a,h)anthracene		X	1	4 64	10	A . S M. ST		AP. F						
20B. 1,2-dichlorobenzene		X		10 0		Service Contract								
21B. 1,3-dichlorobenzene		X		- 10										

							Se See S	VAL	J98820 ²	1210		1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	OUTPAL I	NO
V. INTAKE AND EFFL	UF	NT (HARACT	FRISTIC	cs								OUTFALI 006	
PART C (CONTINUED)	-0-		711741040	21110111						The same	Sta.			
PART C (CONTINUED)	12.8	Mark 'X			3. EFFLUE	NT				4. UN	ITS	5. 11	NTAKE (or	otional)
	2. 1	Idik A	a. MAXIMUM I	AILY VALUE	b. MAXIMUM 30		UE C. LONG TERM AVRG. VALUE		100	(specify if blank)		a. LONG TERM AVRG. VALUE		
1. POLLUTANT	a. Testing Required b. Believed Present c. Believed	Present C. Believed	(1) Concentration	(2) Mass	(1) Concentration	(2) Mass	(1) Concentration	(2) Mass	d. No. of Analyses	a. Concentration	b. Mass	(1) Concentration	(2) Mass	d. No. of Analyses
GC/MS FRACTION BASI	E/NE	UTR	AL COMPO	UNDS (cor	ntinued)									
22B. 1,4-dichlorobenzene		X												100
23B. 3,3-dichlorobenzidine		X					1000000	I Con		A.		DE STORY		
24B. diethylphthalate		X										DESTRUCTION OF THE PERSON OF T		
25B. Dimethylphthalate		X							400					
26B. di-N-Butylphthalate		×					WHO THE	100	I Services					
27B. 2,4-Dinitrotoluene		X				1		VIA.						
28B. 2,6-dinitrotoluene		×				All	NA.		Maria					
29B. di-N-Octyl Phthalate		×				A.		V						
30B. 1,2-Diphenylhydrazine		X				- VA	100							
31B. Fluoranthene		×					In All		1000					
32B. Fluorene		×		10.18	-090m		1							
33B. Hexachlorobenzene		×			1		A.							
34B. Hexachlorobutadiene		×			Bar Bar									
35B. Hexachlorocyclopentadiene		×			Tour P	-			1000					
36B. Hexachloroethane		×		495000										
37B. Indeno(1,2,3-cd)Pyrene		×			A CO	-01								
38B. Isophorone		×		W.	10 -									
39B. Naphthalene	10	×	coffice		The same of									
40B. Nitrobenzene	100	×		AF NO		300								
41B. N-Nitrosodimethylamine		×		10	4 Land		CE SE FE		1000		1000			1 443
42B. N-Nitrosodi-N-Propylamine		X											AND VALUE	

								VAL	1988204	1210	Author St. A.	Park Calle		
V. INTAKE AND EFF	LUENT	CH	HARACTI	ERISTIC	S								OUTFALI 006	
PART C (CONTINUED)					20 Page 18		, 25			NAME OF THE PERSON OF THE PERS	No.			Vie
Trace of (Continueday)	2. Mark	'X'	7 30 10		3. EFFLUE	NT	1 - C - C - C - C - C - C - C - C - C -			4. UN	ITS	5. 1	NTAKE (o	otional)
	2. 1		a. MAXIMUM DAILY VALUE		b. MAXIMUM 30 DAY VALUE		c. LONG TERM AVRG. VALUE		100	(specify if blank)		a. LONG TERM AVRG. VALUE		
1. POLLUTANT	a. Testing Required b. Believed Present	c. Believed Absent	1) Concentration	(2) Mass	(1) Concentration	(2) Mass	(1) Concentration	(2) Mass	d. No. of Analyses	a. Concentration	b. Mass	(1) Concentration	(2) Mass	d. No. of Analyses
GC/MS FRACTION BAS	SE/NEUT	RAL	COMPOU	NDS (con	tinued)									
43B. N-Nitrosodiphenylamine		Х												The same of
44B. Phenanthrene		X						State of the last		W				
45B. Pyrene		X							Stan				EHLERS.	
46B. 1,2,4-trichlorobenzene		Х					N. A.			***************************************				
GC/MS FRACTION PES	STICIDES	3												
1P. Aldrin		X				69		NA.						
2P. a-BHC		Х	and the second			AST	10	10						
3P. b-BHC		Х				10		Y						
4P. g-BHC		X				10	100							-
5P. d-BHC		Х				N	1		25 4 5					
6P. Chlordane		X			artifies.		No. of							
7P. 4,4-DDT		X			9		-							
8P. 4,4-DDE		Х	No. of the last		M. Re	litte.							1000	
9P. 4,4-DDD		Х			Tour State of the	10		1000						
10P. Dieldrin		X		4500					1999		alt to the			
11P. a-Endosulfan		Х			A FOR	19								
12P. b-Endosulfan		Х		- MA	1							100000		
13P. Endosulfan sulfate		х	1000	(A)				Mary E.	100					
14P. Endrin		Х	A Property	A VA	M									
15P. Endrin Aldehyde		х		10 1					100					
16P. Heptachlor		X	A	MA.										

V. INTAKE AND EF	FLUENT C	HARACT	ERISTIC	cs					Annual Control			OUTFALI 006	
PART C (CONTINUED)									The same of	Ran.			
	2. Mark 'X'			3. EFFLUE	NT				4. UN	ITS	5.1	NTAKE (or	ptional)
		a. MAXIMUM DA	AILY VALUE	b. MAXIMUM 30		c. LONG TERM	VRG. VALUE	1507	(specify	f blank)	a. LONG TERM A	VRG. VALUE	GIVE N
1. POLLUTANT	Required D. Believed Present C. Believed Absent	(1) Concentration	(2) Mass	(1) Concentration	(2) Mass	(1) Concentration	(2) Mass	d. No. of Analyses	a. Concentration	b. Mass	(1) Concentration	(2) Mass	d. No. of Analyses
GC/MS FRACTION PE	STICIDES (continued)											
17P. Heptachlor Epoxide	X												
18P. PCB-1242	X												
19P. PCB-1254	X							2			The state of		
20P. PCB-1221	X						M						
21P. PCB-1232	X												
22P. PCB-1248	X												
23P. PCB-1260	X				109	ALC: NO.							No.
24P. PCB-1016	X				The same								No.
25P. Toxaphene	X				1								

Figure 1









Figure 2



Note: All flow values provided in Figure 2 are representative of the previous permit term. Plant operation during the current permit term was atypical and flow data do not characterize normal plant operation. Flow data measured over the current permit term are summarized in Appendix D. See Appendix A Note 2 for a further description of the given flow values.

Appendix A Notes

Note 1: FACILITY OPERATION AND FORM 2C ALANYTICAL DATA

As indicated by the summary of the Discharge Monitoring Reports (DMRs) included in Appendix D, the Plant has had limited operation during the current permit cycle and has not operated since the January–March 2011 monitoring period. In their current state the generating units are inoperable. Under these circumstances there is no discharge from the facility other than stormwater and it was not possible to obtain effluent samples from the outfalls. For this reason, the analytical data included on Form 2C for Outfalls 001, 002, 003, 004, 005, and 006 are the data collected and analyzed by Water Chemistry, Inc. during the previous VPDES renewal cycle in 2008. Flow values included on Form 2C Items II-A and II-B are from the previous renewal application and reflect normal operation.

Note 2: FORM 2C ITEM II, A, B - DISCUSSION OF FLOW FIGURES FROM ITEM II-A (FLOW DIAGRAM) AND ITEM II-B (DESCRIPTION, TREATMENT, SOURCES, ETC.)

The flow figures designated as average flows in the water balance diagram (Figure 2), and included on Form 2C, Item II-B, Column 2b, represent the volume of water necessary to operate this plant under normal conditions at full capacity. The Company contends that figures based on any other method of calculation would be misleading and not in keeping with the intent of Form 2C. The generating scheme at this and other hydroelectric plants is determined by a number of factors, the most important of which are availability of water and the system availability of generating units. Therefore, a large number of variables directly impacting these two factors can affect the generating schedule, making it difficult to accurately predict the operating schedule, and thus the flow scheme for a hydroelectric unit based on historical records. Because of this, the figures included on the application represent the flows that would be expected on any given day when all units are operating at full capacity. The use of flow data determined by any other method would restrict the Company's ability to operate the plant at full capacity, thereby derating the capacity of the plant. These figures do not represent maximum design flows in that such factors as redundancy and extraordinary operations were not used in the calculation of listed flows, as these are atypical of normal operation.

Actual flow rates for Outfalls 001-005 are unavailable due to the inaccessibility of the discharge points. The flows ascribed to these outfalls on Form 2C were calculated using a combination of intake measurements and engineering estimates based on available system data as described below. Outfall 006 flows reported on Form 2C are from the previous renewal application. Flow values reported under the current permit term are summarized in Appendix D.

The reported flows for Outfalls 001, 002, and 003 (Units 1, 2, and 3 intermediate bearings, respectively) were calculated using best engineering practices based on the flows measured at the thrust bearings and the sump (Outfall 006). The flows

on these three units should be equal due to their like design. The discharge piping from the generator coolers discharges to the plant sump where it is gravity fed to the intermediate bearings of Units 1, 2, and 3. The supply lines to the generator cooler discharge and to the intermediate bearings all measure one inch in diameter, and there is no significant difference in head pressure between these locations. In addition, the generator cooler discharges are the major source of water feeding the sump which supplies cooling water to the intermediate bearings. All of these factors were taken into account in determining the flow figures for these outfalls.

Flow to the Units 4 and 5 intermediate bearings (Outfalls 004 and 005, respectively) was measured using a Material Control Inc. Ultrasonic Flowmeter Model #CW-603 for the original VPDES permit application submittal in 1993. Since there is a single supply for the water cooling each unit's bearing, and a single point where water may be discharged, it can be concluded that the quantity of water discharged from the bearings to the tailrace is equivalent to the intake flow.

The average flow reported for Outfall 006 (sump overflow) is based on the average of the quarterly flow measurements taken over the previous permit term, as described in Note 1, using a 5-gallon bucket and a stopwatch. Data collected over the current permit term are summarized in Appendix D. The maximum flow for this outfall was estimated by determining the maximum flow for the plant service water inlet header and assuming that this entire flow was discharged to the sump through the generator coolers/thrust bearing coolers and the fill valve. Other sources that could supply water to the sump, such as the emergency eyewash and shower on the 'A' building main floor, operate on such an infrequent basis as to render their contribution to this discharge negligible. The flow for the #1 air compressor aftercooler in the flow diagram and flow description was determined for the original VPDES permit application in 1993 using a combination of actual flow measurements in conjunction with a time meter to establish the actual time in operation over a 24-hour period.

Note 3: STORMWATER

In addition to the outfalls listed in Form 2C Item I, there are at this facility a number of pipes, culverts, etc. which carry uncontaminated stormwater collected from roof and deck drains, yard areas, employee parking lots, and other areas not directly associated with the production functions of the plant. The Company submits that these drains do not fit the definition of "discharges associated with industrial activities", therefore, should not be included in this permit. For this reason, these drains were not sampled during permit application preparation, and have not been specifically identified in this application.

Note 4: LEAKAGE AND SCREEN WASH

Each of the three intake pumps at Reusens Plant is fitted with filter screens to remove debris from the intake water prior to use. Periodically (dependent upon river conditions), these screens require cleaning to remove accumulated debris. When necessary, the screens are cleaned in the basement area of the plant using river water from one of the intake pumps. The accumulated mud and debris removed from the screens is collected and properly disposed, while the water is pumped via a sump pump back to the James River. In addition, this sump pump is used to remove any leakage in the basement area resulting from high river conditions. Any water in the basement would not come in contact with any plant process or equipment, other than the intake screens. The Company does not believe that this water should be regulated in the permit, as it is not a discharge or addition of pollutants to navigable waters, as contemplated by the Clean Water Act, and does not constitute an outfall.

Note 5: LOWER BEARINGS

Because of the length of the shaft connecting the generator to the turbine, each of the units at Reusens Plant requires two guide bearings to prevent excessive movement of the shaft. The intermediate bearings are located about ten feet below the level of the forebay and require cooling water that is delivered through a discrete cooling water system. The lower guide bearings positioned just above the turbine do not require a separate system for cooling. Instead, their position in the water (approximately 18 feet below the forebay) allows these bearings to depend on the pressure differential between the tailrace and forebay to force the surrounding water through the small (~0.02 inch) opening between the bearing and the shaft. This water lubricates the bearing, reducing friction and preventing bearing deterioration. Contact between the water and turbine generators is limited to the stainless steel shaft and the bearing itself, composed of inert plastic. The Company does not believe that this water should be regulated in the permit, as it does not constitute a discharge or addition of pollutants, as contemplated in the Clean Water Act, and is not an outfall.

Note 6: UNITS 4 AND 5 GOVERNOR AND DRAIN VALVE SHAFT LEAKAGE

All five units at Reusens Hydro are considered wet turbines. This means that the turbines, associated shafts, and mechanics are located in a wet well completely submerged underwater. The forebay water level is higher than the turbine systems. The water pressure associated with the higher forebay water level results in water leakage through packing glands associated with the turbines' governor and drain valve shafts. The governor shafts operate the wicket gates that regulate flow of water to the turbines, while the drain valve shafts open and close the drain valves located at the bottom of the turbines. These drain valves are used to drain the last six to eight feet of water from the systems during outages.

In the past, for Units 4 and 5, this leakage flowed across a concrete floor exposed to the outside, and back to the river. In the winter this water would sometimes freeze, while in the summer it occasionally caused excessive algae growth. Both situations created safety hazards for individuals traversing this concrete floor. To eliminate this safety hazard, a coupling was placed at the locations where the leakage came through the concrete floor to collect the water. The water is transferred from these couplings to the river via PVC pipes.

No monitoring data or Form 2C has been completed for these discharges. The Company submits that this leakage should not be regulated under the VPDES program. The leakage simply involves the passing through of water from the upstream side of the dam or powerhouse to the downstream area. The leakage water, like generating water, does not come into contact with any plant processes that may result in the addition of pollutants from outside sources, and thus does not conform to the definition of pollution under the Clean Water Act.

Note 7: ESTIMATION OF DATA IN PART V-A, B, AND C FOR OUTFALLS 001, 002, 003, 004, AND 005

Outfalls 001 through 005 discharge underwater directly to the tailrace. As a result, these discharge points are inaccessible for obtaining effluent samples. There is no reason to believe that any additional contamination to intake water occurs when passing through the intermediate bearings (see Appendix B for further description). Consequently, the estimates provided for chemical concentrations at Outfalls 001, 002, and 003 in Part V-A, B, and C were taken directly from concentrations measured at the sump (Outfall 006) during the previous renewal sampling and discharge monitoring, from which water is supplied to the intermediate bearings. The data provided for Outfalls 004 and 005 were estimated directly from concentrations measured in samples of the intake water to these units.

Note 8: REQUEST FOR REDUCED MONITORING FREQUENCY

Under the present VPDES permit, the Company monitors flow, pH, and temperature on a quarterly basis on Outfall 006. Data collected to date during the term of this permit are provided in Appendix D.

The Company submits that these data demonstrate that this discharge contributes negligible warming to the James River downstream of the facility, and has no reasonable potential to cause an exceedance of the James River temperature standard of 32 °C. Of the available monitoring data from both the current and previous permit terms, the highest measured temperature at Outfall 006 was 30.7 °C. For the James River 7Q10 flow at the plant of 319 MGD, the Outfall 006 maximum flow of 0.154 MGD would have to undergo a temperature rise of about 239 °C to produce a change of 0.1 °C in the ambient river temperature. Based on

this discussion, the Company requests that the monitoring frequency for Outfall 006 be reduced to once per year in the next permit, with measurements to be made during the months of July or August, when river temperatures are most likely to approach the 32 °C standard.

Similarly, the pH monitoring data for Outfall 006 have demonstrated consistent compliance with the 6.0-9.0 acceptable range. Of the available monitoring data from both the current and previous permit terms, the actual range of pH measurements from Outfall 006 is 6.88-8.45.

Appendix B Outfall Descriptions

I. LIKE OUTFALLS

The Reusens Hydroelectric Plant is made up of a dam and two buildings containing five 3,125-kilowatt units. All five units are very similar in design and the materials of construction. All are "run-of-river" units, with the generation load dependent upon the quantity of available water, and the mechanical availability of the units themselves. Typically, no one unit is run either more frequently or more consistently than the other four. The exception is prolonged outages.

Five of the six outfalls are comprised of discharges from the intermediate guide bearings. Regardless of the unit, the intermediate bearings' function is to maintain shaft alignment. The discharges from these five units can be divided into two groups according to the influent source. Unit 1, 2, and 3 intermediate bearings are gravity supplied with cooling water from the sump. The water in the sump includes cooling water from other sources, so that it may be somewhat different from water supplied directly from the intake pumps. However, after the water leaves the sump, it enters a closed cooling water system that supplies the Unit 1, 2, and 3 intermediate guide bearings. As a result, water quality should be consistent among the three units. Any change in intake quality should affect each of the units in the same manner.

Water delivered to the intermediate bearings on Units 4 and 5 is supplied directly by the plant's intake pump through a closed system that allows no contact between the cooling water and the generating equipment, other than the stainless steel shaft and the plastic bearings. There is little likelihood of contamination, and the water quality of these two discharges should be identical.

For these reasons, the Company requests that each group of cooling water systems having an identical intake water source be considered like discharges for the purposes of this permit. These would be categorized as follows:

Group 1

- Intermediate Bearings Unit 1
 Intermediate Bearings Unit 2
 Outfall 001
 Outfall 002
 Intermediate Bearings Unit 3
 Outfall 003
- Group 2
 - Intermediate Bearings Unit 4 Outfall 004
 Intermediate Bearings Unit 5 Outfall 005

II. FURTHER DESCRIPTION OF OUTFALLS

Outfalls 001, 002, 003, 004, & 005: Intermediate Guide Bearings

The turbine shaft, connecting the turbine to the generator, is held in place by two guide bearings, or alignment bearings: the intermediate guide bearings and the lower guide bearings. The clearance between the bearings and the shaft is 0.020 inch, and requires water for lubrication to reduce the detrimental effects of friction. The lower guide bearings are positioned so that they can use water from the surrounding environment to provide this lubrication. The water is pushed into the opening between the shaft and the bearing by the pressure differential created by the difference between water level in the forebay and the tailrace.

The intermediate bearings are located on the shaft at a level approximately ten feet below the forebay. The difference in head, by itself, is not sufficient to force the water through the gap between the shaft and these bearings. Consequently, water must be piped into this area to provide the necessary lubrication.

Outfalls 001, 002, 003, 004, and 005 result from the discharge of this water into the James River as it exits the intermediate bearings. As discussed in Appendix A Note 7, the discharge points are underwater and are inaccessible. Consequently, it was not possible to obtain samples from any of the five guide bearing discharges. The cooling water in question only contacts the piping carrying it to the intermediate bearings, the shaft of the turbine, and the shaft alignment bearing; thus, there is no reason to believe that analyses of these discharges would yield results different from those presented in Part V-A, B, and C for the sump discharge that supplies water to this bearing on Units 1, 2, and 3, or from the intake that directly feeds Units 4 and 5.

Outfall 006: Sump

The sump at Reusens Plant (capacity ~30,000 gallons) is designed to accept discharges from the Units 1, 2, and 3 generator coolers and thrust bearing coolers. The effluent from the #1 air compressor aftercooler, as well as an emergency shower and eyewash station on the main floor of the "A" building, also discharge into the sump. In turn, this sump provides water to the intermediate bearings on Units 1, 2, and 3. The water contained in this sump may be used to operate equipment for a short time period in the event of an intake pump failure. All of the water exiting the sump is gravity fed.

The overflow from the sump (Outfall 006) is discharged into the tailrace by gravity through a pipe located on the east side of Building "A". In addition to the overflow pipe, a drain is also located at the bottom of the sump should it be required to completely empty the sump. This drainpipe is kept closed under normal operating conditions, and would only be used under extraordinary circumstances.

Appendix C

Approved 8-Hour Composite Sampling during Previous Renewal (2008)

Approved 8-Hour Composite Sampling during Previous Renewal (2008)

As described in Appendix A Note 1, the analytical data provided on Form 2C Part V for Outfalls 001, 002, 003, 004, 005 and 006 were collected during the previous VPDES permit renewal (2008). Per Item V.B (Sampling) of Form 2C Instructions (Page 2C-1), the Company requested a waiver to the 24-hour composite sampling requirement for BOD₅, Total Suspended Solids, Chemical Oxygen Demand, Total Organic Carbon and Ammonia during the previous permit renewal cycle. Instead of 24-hour composite sampling and subsequent analysis for the aforementioned parameters, 8-hour composite sampling was conducted for the 2008 VPDES renewal sampling.

Appendix D Summary of Discharge Monitoring Reports

Summary of Discharge Monitoring Reports at Outfall 006 from July 2009 through September 2013

Summary of DMR Data Collected at Outfall 006

Monitoring Period	Flow (MGD)	pH (SU)	Temperature (C°)
07/01/2009 - 09/30/2009	0.034	7.7	27
10/01/2009 - 12/31/2009	0.029	8.0	21
01/01/2010 - 03/31/2010	0.004	7.4	8
04/01/2010 - 06/30/2010	0.029	7.6	20
07/01/2010 - 09/30/2010	NR	NR	NR
10/01/2010 - 12/31/2010	0.001	8.2	10
01/01/2011 - 03/31/2011	0.003	8.3	8
04/01/2011 - 06/30/2011	NR	NR	NR
07/01/2011 - 09/30/2011	NR	NR	NR
10/01/2011 - 12/31/2011	NR	NR	NR
01/01/2012 - 03/31/2012	NR	NR	NR
04/01/2012 - 06/30/2012	NR	NR	NR
07/01/2012 - 09/30/2012	NR	NR	NR
10/01/2012 - 12/31/2012	NR	NR	NR
01/01/2013 - 03/31/2013	NR	NR	NR
04/01/2013 - 06/30/2013	NR	NR	NR
07/01/2013 - 09/30/2013	NR	NR	NR

^{*}NR signifies no discharge from the outfall due to unit outages.

VPDES Permit Application Addendum

VPDES Permit Application Addendum

- · · · · · · · · · · · · · · · · · · ·	ed: Appalachian Power Company
Who will be legally responsible for the wastewate not be the facility or property owner.	er treatment facilities and compliance with the permit? This may or may
2. Is this facility located within city or tow	vn boundaries? Yes 🗵 No 🗌 City of Lynchburg
3. Provide the tax map parcel number for	r the land where the discharge is located. 13701001
4. For the facility to be covered by this pe	rmit, how many acres will be disturbed during the next
five years due to new construction activiti	es? 0 acres
5. What is the design average effluent flo	us of this facility? 0.140* MCD
	w of this facility? 0.140* MGD ax. 30-day average production level, include units:
· -	ge flows excluding stormwater over previous VPDES permit term.
In addition to the design flow or production other discharge flow tiers or production If "Yes", please identify the other flow tiers.	
Please consider the following questions for both expand operations during the next five years? Is	the flow tiers and the production levels (if applicable): Do you plan to your facility's design flow considerably greater than your current flow?
6. Nature of operations generating waster	vater:
Hydroelectric power generation non-contact	et cooling water
0 % of flow from domestic connection	as/sources
Number of private residences to be served	
100 % of flow from non-domestic conne	ctions/sources
7. Mode of discharge : X Continuous Describe frequency and duration of interpretable in the continuous of the continuo	☐ Intermittent ☐ Seasonal termittent or seasonal discharges:
8. Identify the characteristics of the received discharge point:	ving stream at the point just above the facility's
X Permanent stream, never dry	
Intermittent stream, usually flowing	g, sometimes dry
Ephemeral stream, wet-weather flow	w, often dry
Effluent-dependent stream, usually	or always dry without effluent flow
Lake or pond at or below the discha	urge point
Other:	
9. Approval Date(s):	